Ceiling Speaker
T-104U T-105U T-106U

- Power taps @100V 1W, 1.5W, 2W, 3W, 6W, 9W
- Power taps @70V 0.5W, 1W, 1.5W, 3W , 4.5W
- Built-in 100V/70V transformer
- In-ceiling type loudspeaker
- Metal grille & ABS baffle
- Spring clip fast installation

Frameless Ceiling Speaker
T-205T T-206T T-208T

- Rated power (100V) 1.25W, 2.5W, 5W,7.5W, 10W, 15W, 20W,30W
- Rated power(70V) 0.65W, 1.25W, 1.87W, 2.5W 3.75W, 5W, 7.5W, 10W,15W
- Built-in 100V/70V transformer
- In-ceiling type loudspeaker
- Plastic shell + metal grille
- Fast installation by spring clip

Weatherproof Horn Speaker
T-720A

- Power Taps @100V 15W, 30W
- Power Taps @70V 7.5W, 15W
- Built-in 100V/70V transformer
- Waterproof projector type loudspeaker
- IP66 waterproof level
- ABS enclosure and metal bracket

Uni-directional Projection speaker
T-770

- Power Taps @100V 7.5W, 15W
- Power Taps @70V 3.75W, 7.5W
- Built-in 100V/70V transformer
- Waterproof projector type loudspeaker
- 6" full range speaker unit
- IP66 waterproof level
- Aluminum enclosure and metal bracket

info@itc-pa.com.cn

Wall-mount Speaker
T-774H T-775H T-776H T-778H

- Power taps @100V 2.5W, 3.75W, 5W, 7.5W, 10W, 15W, 20W, 30W, 40W, 60W
- Power taps @70V 1.25W, 1.9W, 2.5W, 3.75W, 5W, 7.5W, 10W, 15W, 20W, 30W, 40W, 60W
- Built-in 100V/70V transformer
- Wall-mount type loudspeaker
- Metal grille,ABS enclosure and stainless mounting bracket

Outdoor Column speaker
T-701A T-702A T-703A T-704A

- Power taps @100V 5W, 10W, 15W, 20W, 30W, 40W
- Power taps @70V 2.5W, 5W, 7.5W, 10W,15W, 20W
- Built-in 100V/70V transformer
- Weatherproof column type loudspeaker
- IP66 waterproof level
- Aluminum enclosure & grille in white
- A pair of metal mounting brackets are supplied

T-205A/T-206A/T-208A

T-206CH

T-601

T-865CF

T-4535C

T-200DW

T-710K

TS-108HT





www.itctech.com.cn

Audio Amplifier & Speaker

Tabletop Mini Mixer Amplifier with MP3/Tuner/Bluetooth

T-B40 T-B60 T-B120 T-B240

- Rated power: 40W, 60W, 120W, 240W
- With 6.3 mic input and RCA line input, for different options
- MIC input, with independent volume cintrol
- Line input with independent volme, and 1 EMC input
- With Auto playback for MP3 and power-off memory function
- With Tuner and Bluetooth function
- Priority: MIC 1 input prior to all other line inputs
- Indicator light for power, signal, overload, protectionand and for 100V output

Tabletop Digital Mixer Amplifier with MP3/Tuner/Bluetooth

T-120DM T-240DM T-350DM T-500DM

- Rated power: 120W, 240W, 350W, 500W
- Desktop design, exquisite SMT process design
- Support MP3/Tuner/Bluetooth remote control function, and the control distance can be up to 8 meters
- With USB interface and SD card interfcae, integrated MP3 player module, with automatic priority playing audio function, digital screen can display the current palying track of USB
- Integrated Bluetooth module to support music playback via Bluetooth of the mobile phone
- Each input has indepemdent volume adjustment, and the master volume has treble, bass adjustment and volume control function
- MIC1-4 balanced input, built-48V phantom power supply
- Output: 100V, 4-16Ω

Class D Mixer Amplifier with MP3/Tuner/Bluetooth (Phone jack mic input)

T-60DTB T-120DTB T-240DTB T-350DTB T-500DTB

- Rated power:60W,120W,240W,350W,500W
- Standard cabinet design (1U), exquisite SMT process design
- Support MP3/Tuner/Bluetooth remote control function, and the control distance can be up to 8 meters
- With MP3 function module, adopt LCD display, support playback of various file formats in USB disk such as MP3, WMA, APE, FLAC, WAV, and AAC; with TF card, and can display song names
- Integrated Bluetooth module to support music playback via Bluetooth of the mobile phone
- Equipped with level indication, overload and protection indicator
- Output:100V, 4-16Ω

Class D Mixer Amplifier with MP3/Tuner/Bluetooth (Phoenix mic input)

T-B60DTB T-B120DTB T-B240DTB T-B350DTB T-B500DTB

- Rated power:60W,120W,240W,350W,500W
- Standard rack mounted design (1U), SMT technology
- Support MP3/TUNER/Bluetooth remote control function, and the remote control distance is up to 8 m
- With MP3 function module, adopt LCD display, support playback of various file formats in USB disk such as MP3, WMA, APE, FLAC, WAV, and AAC; with TF card, and can display song names
- Integrated Bluetooth module to support to play music via Bluetooth mobile phone
- Equipped with level indication, overload and protection indicator
- Output:100V, 4-16Ω

5 Zones Digital Mixer Amplifier with MP3/Tuner/Bluetooth

TI-120DTB TI-240DTB TI-350DTB TI-500DTB

- Rated power: 120W,240W,350W,550W
- Standard rack mounted design(1U) with delicate SMT technology
- With MP3/TUNER/Bluetooth, songs being played can be shown on the digital screen
- With MP3/TUNER/Bluetooth remote control function
- 1 EMC input, 2 AUX inputs, 4 MIC inputs
- Channel priority function EMC>MIC1>MIC2, MIC3,AUX1, AUX2
- Each input has independent volume adjustment,and the master volume with treble, bass adjustment and volume control
- With electrical level and overload protection indicator
- The device has good self-prorection such as short cercuit, overload and overheat
- Perfect combined design for high efficiency& energy saving switch power and class-D amplifier, with high stability
- Voltage Power Supply: 220V-240V
- 24VDC power supply optional
- Output: 100V,4-16Ω

2 Channel Mixer Amplifier with Effector and MP3/Bluetooth

TS-2060WV TS-2120WV

- Two channels audio input, with switching function.
- Three channels microphone input with independent gain adjustment function.
- With professional digital echo delay circuit to make the voice more natural.
- MP3 player with SD/USB interface, with Bluetooth and digital display function
- With MP3 recording function, songs and speech can be recorded and played by MP3
- 60W×2/120W×2 @100V output, can be connected with two groups of speakers.
- With forced cooling fan to enhance the rejection of heat, can be long time working.
- Using 1U chassis design, with switching power supply and type H power amplifier chip combination, efficient, light weight, beautiful appearance.

1/2/4 Channel Class-D Power Amplifier

T-1120DS T-1240DS T-1350DS T-1500DS T-2120DS T-2240DS T-2350DS T-2500DS T-4120DS T-4240DS T-4350DS T-4500DS

- Rated power:1*120W,1*240W,1*350W,1*500W
  2*120W,2*240W,2*350W,2*500W
  4*120W,4*240W,4*350W,4*500W
- Built-in high efficiency switching power supply
- Reasonable heat dissipation to maintain a working temperature lower than 55 degree
- With fault output function to remotely monitor the working state of amplifier
- Output: 100V, 4-16Ω

6 Zones Digital Mixer Amplifier with MP3/Tuner/Bluetooth

TI-1206S TI-2406S TI-3506S TI-5006S

- Rated power: 120W,240W,350W,550W
- 4 channel Mic inputs, 2 channer line inputs, separted treble and bass control
- 6 zones output, separate zone volume control
- Built-in chime, the chime is optional, 4 tones and 2 tones with alarm generator
- With MP3 function module, adopt LCD display, support plauback of various file formats in U disk such as MP3, WMA, APE, FLAC, WAV, and AAC; with TF card, support moblie phone Bluetoth function, and can display song names
- Built-in 24VDC
- MIC1-4 built-in 48V phantom power and independent volume control
- T-216 remote microphone can remote control zone output, maximum cascade to 6 mics
- The audio input with separate control, tone control and master volume control
- Five priority levels: EMC>TEL/Remote MIC>built-in chime>MIC1>MIC2-4, LINE1-2

2/4 Channel Matrix Digital Mixer Amplifier with MP3/ Tuner/Bluetooth

T-2120UC/T-2240UC/T-4120UC/T-4240UC

- 120W/240W constant impedance/voltage high performance digital power amplifier (4-16Ω/100V) with 2/4 channel outputs
- Built-in MP3 recording function
- 6 inputs independent volume control
- 1-4 input with adjustable gain control
- 2/4-channel outputs support independent tone control
- Support 2/4 remote microphone T-214B
- Built-in MP3 (U disk/SD card) player function
- Built-in FM radio function
- Built-in Bluetooth function and high-gain Bluetooth antenna to connect to mobile phones / computers
- Adopt 2.4-inch high-grade TFT screen
- 2/4 channel outputs support remote control panel T-651
- Distortion, protection, signal, output status indicator
- 1-4 inputs channels support phantom power

1/2/4 Channel Class-D Power Amplifier

T-1120D T-1240D T-1350D T-1500D T-2120D T-2240D T-2350D T-2500D T-4120D T-4240D T-4350D T-4500D

- Rated power:1*120W,1*240W,1*350W,1*500W
  2*120W,2*240W,2*350W,2*500W
  4*120W,4*240W,4*350W,4*500W
- 1/2/4 channel class-D digital power amplifier
- The rear panel is equipped with a “ground” line suspension switch, which effectively eliminates the loop noise caused by the connection of the “ground” lines of multiple equipment signals
- 85% high efficiency amplifier, low power loss, low heat
- With European terminal balanced input and output
- Remote control of power-on function: remotely turn on the power and disconnect the power when both functions are turned off at the same time
- Fault output function, remote monitoring power amplifier working state
- With 24V standby power inverter function, power amplifier with voltage limit, short circuit, overload, overheat protection