



Description

The paperless server, working with the management software, is responsible for processing pre-meeting information presets such as meeting function modules, meeting themes, participant information, meeting topics, and voting content. In addition, it supports application functions such as uploading and sharing of various meeting documents, personnel permission management, and real-time recording of meeting information.

Feature

- * Industrial-grade cabinet design, steel structure cabinet, with high anti-magnetic, dust-proof and shock-proof capabilities.
- * 17.3-inch 1080P full HD display screen, user-friendly touch screen control.
- * Built-in industrial-grade push-pull keyboard, built-in industrial-grade touch mouse and panel + left and right button design, support connecting external mouse and keyboard through USB interface or PS/2 interface, convenient for users to operate.
- * Industrial-grade dedicated motherboard design, Intel Core i7 quad-core processor, faster processing speed, stronger operating performance, long-term stable and uninterrupted work.
- * Designed with 6 USB interfaces, 6 universal serial ports, the highest transmission rate is 480M, convenient for external extension of peripheral equipment access.
- * With 2 Gigabit network cards, compatible with 100M network at the same time, adaptive switches to connect the system.
- * With 1 short-circuit triggering start-up operation interface, used for external equipment to drive the start-up operation at regular intervals to realize the unattended function.

Specification

Model	TS-8300D
CPU	i7 (Quad Core) (The product performance will continue to be optimized due to continuous product upgrades)
Memory	8G
Hard disk	Enterprise 1TB
Network interface	2×Gigabit network interface (Rj45)
Audio interface	1×3.5mm audio input interface, 1×3.5mm audio output interface, 1×3.5mm MIC interface
Other interfaces	2×PS/2 ports, 6×Serial ports, 1×VGA, 1×DVI, 6×USB ports
Display screen	17.3-inch high resolution LED LCD screen (1920*1080)
Touch screen	10-point capacitive touch screen
Working environment	0°C-60°C, 10% ~ 95% (no condensation)
Storage temperature	-20°C-70°C, 5% ~ 95% (no condensation)
Working power	AC100V-240V
Dimension (L×W×H)	484×303×353.5mm (Without handle)
Weight	18.4kg
Color	Black