



## TS-FE173ZMT



### Description:

The integrated design of the lift and the array microphone, without back board connection, looks neat and elegant. It can work with the paperless conference terminal to display the required patterns and other information. The machine can perfectly realize the powerful interactive paperless conference function with the array microphone.

### Feature:

- \* Dual-screen design, the rear 11.6-inch vice screen.
- \* The machine adopts an all-aluminum structure, high-quality aluminum material and CNC engraving processing treatment; the overall display frame and the cabinet adopt aluminum alloy, making the overall machine exquisite, light, beautiful.
- \* The surface of the machine is anodized and looks bright.
- \* The panel is space-saving with 3mm in thickness only. It is only one-third weight of the conventional lift, which reduces transportation cost and the pressure of conference table.
- \* The transmission structure is specially treated to minimize the noise; it adopts high-quality stretch-resistant belts, high-precision sliding guide rail and linear bearings, and AC gear motor as the driving power; the central control protocol, with strong compatibility, can be compatible with all computer controllers. The screen is powered on when turning up, and is powered off when turning down, which is environment friendly.
- \* Support HDMI and VGA two-channel signal input. When there is only one signal input, the screen will automatically recognize the signal. When two signals are input at the same time, it can be manually switched through the panel buttons. When no signal input, the screen will automatically enter power saving mode.
- \* This machine can be centrally controlled by the central control software and the controller. One key can make all the machines in the room go up or down.
- \* 48KHz sampling rate, clear and bright sound, better than the CD sound quality, no low-frequency impact sound.
- \* The delegate unit has the functions of speech timer and speech stopwatch; the chairman unit has the function of speech stopwatch, and its speech time is not limited.
- \* The delegate unit has the function of applying for speech, and the application can be approved by the chairman unit with a screen or with a "3" key, or by the PC software.
- \* 5-band EQ adjustment function, can adjust different sound effects according to the voice characteristics of the speaker until the perfect effect is achieved.
- \* The chairman unit has priority function to turn off all delegate microphones that are speaking;
- \* 100M network transmission, hand-in-hand cascade, long-distance transmission, and perfect sound quality.
- \* Non-gooseneck microphone pickup, the array pickup distance can reach 60cm. Good directivity, cystic pickup area, effectively avoid the surrounding noise pickup.
- \* Electric flip structure, which can be flipped up when speaking, and down when not speaking. It can be controlled by buttons or unified management by the controller and PC software.

### Array Microphone Feature:

- \* Microphone status indicator;
- \* Connect to the port of the previous conference unit;
- \* Connect to the port of the next conference unit;
- \* 220V power input port of AC power supply;
- \* 220V power output port of AC power supply;
- \* UP button: turn up the microphone;
- \* DOWN button: turn down the microphone;
- \* ON/OFF button: turn on/off the microphone.

### Specifications:

Model	TS-FE173ZMT
Screen	Touch control
Lifting time	30S
Elevation angle	30
Product size	467*130*565mm
Cabinet size	461*126*562mm
Panel size	476*130*3mm
Desktop opening size	463*127(recommended to open hole according to the actual product)
Panel sinking size	477*131*3mm(recommended to open hole according to the actual product)
Environment conditions	according to the actual product -20℃~50℃; humidity≤70%
Screen size	17.3 inches
Screen ratio	16:9
Screen resolution	1920*1080
Video port	VGA, HDMI
Video switching	VGA, HDMI (switch manually)
Screen contrast	700:1 (Typ.) (TM)
Screen brightness	300 cd/m <sup>2</sup> (Typ.)
Viewing angle	89/89/89/89 (Typ.)(CR≥10)
Power supply	AC 220V 50-60/HZ
Signal system	EDP

### Vice screen specification:

Size	11.6 inches
Screen	Not a touch screen
Resolution	1366(RGB)×768 [WXGA]
Contrast	800:1
Brightness	250 (Typ.)
Working environment	Working temperature: 0~50℃; storage temperature: -20~60℃
Working frequency	60Hz
Viewing angle	89/89/89/89 (Typ.)(CR≥10)
Screen type	IPS
Voltage	3.3V
Display size	256.125 × 144 mm (H×V)
Signal system	eDP(1 Lane), terminal, 30 pins

### Array Microphone Specification:

Microphone type	ECM array wired microphone
Microphone core	13
Frequency response	80Hz~16KHz
Input impedance	200Ω
Sensitivity	-30dB (0dB=1V/pa, @1kHz)
SNR	>80dB(A)
Dynamic range	>80dB
Maximum SPL	112dB (THD≤0.5%, @1KHz)
THD	<0.1%
Directivity	Corridor type
Standard	IEC60914
Connector	Six-pin aviation male socket
Power supply	Controller power supply, AC power supply 220V
Sign-in	Key sign in