



# 8-inch Wireless PIP Touch Panel (Hand Held/Desktop)

## TS-9169A



### Description:

TS-9169A is an 8-inch desktop wireless full-color touch screen, used together with a programmable central controller. Colorful and wide screen with 16:9 high-resolution screen. Supports more user-friendly interface like programming images, graphics, text, 2D / 3D buttons etc. In obstacle-free circumstances, wireless transmission distance up to 80 meters.

### Feature:

- \* It has graceful appearance and stable function. 8-inch TFT LCD display and 16:9 high-resolution color (24-bit color depth), clear pictures with high resolution.
- \* It can communicate with central control host through wireless receiver. In obstacle-free circumstances, its wireless transmission distance is up to 80 meters.
- \* The operating interface can be customized by users to be the common image format like PNG, JPG, etc.
- \* Support hand held.
- \* Built-in rechargeable battery and one charge can be used continuously for eight hours.
- \* Resistance touch screen with high sensitivity is adopted, so the operation response is faster.

### Specifications:

	<b>Model</b>	TS-9169A
	<b>CPU</b>	AM3358
	<b>Memory</b>	RAM:256MB; ROM:2GB
<b>Display Screen</b>	<b>Screen Type</b>	TFT LCD
	<b>Size</b>	8.0"
	<b>Resolution</b>	800X480
	<b>Aspect Ratio</b>	16:9
	<b>Color Depth</b>	24 bits 256K color
	<b>Transparency</b>	8 bits alpha channel
	<b>Brightness</b>	450 nit(cd/m2)
	<b>Contrast Ratio</b>	500:1
	<b>Backlight</b>	LED
	<b>Visual Angle</b>	Level $\pm 70^\circ$ , Vertical $\pm 70^\circ$ , $-50^\circ$
<b>Control-Touch Pane</b>	<b>Touch Screen</b>	Resistance-type touch screen
	<b>Switch Type</b>	Power self-lock switch
	<b>Reset</b>	Reset button
	<b>Indicator Light</b>	Power indicator: blue    Signal indicator: green
	<b>Power Port</b>	DC 12V/2A input
	<b>USB Port1</b>	Mini USB
<b>Battery</b>	<b>Battery Capacity</b>	7.4V/4300mAH
	<b>Battery Charging Time</b>	5 Hours
	<b>Charging Temperature</b>	0°C - 55°C
	<b>Battery Specification</b>	Li-ion battery 7.4V
<b>Other Specifications</b>	<b>Loudspeaker</b>	8Ω; 1W
	<b>Wireless RF</b>	433MHz obstacle-free transmission distance 80m
	<b>Static Power Consumption</b>	1.6W(7.4V/216mA)
	<b>Max Power Consumption</b>	3W(7.4V/405mA)
	<b>Dimensions (L*W*H)</b>	238×144×88mm
	<b>Weight</b>	About 1.14KG