



IP Active Speaker

TR-0730



Description:

It is used with the central control system of the small space conference room. Placed in the desktop bookshelf case, it looks neat and beautiful, and the craftsmanship is exquisite, showing a high-end temperament.

Feature:

- * Built-in 1 network hardware audio decoding module to realize the network transmission of 16-bit CD sound quality audio signal.
- * Built-in dual power amplifier, digital woofer, powerful low frequency, high efficiency; analog tweeter ensures soft sound quality.
- * Digital product, easy to expand and not limited by geographical location. There is no need to increase the equipment room management equipment. They adopt the common network free line construction design concept which are easy to install.

Specifications:

Model	TR-0730
Rated power	Woofer 25W, tweeter 2W
Network interface	Standard RJ45 input
Transmission rate	100Mbps
Audio format	MP3
Audio mode	16-bit CD sound quality
Sampling rate	48KHz
Frequency response	70Hz ~ 20KHz (with the local test curve)
THD	≤1%
SNR	>68dB(A) (woofer)
Maximum power consumption	≤60W
Protection circuit	Overload, short circuit protection (woofer)
Working temperature	-10°C~+45°C
Working humidity	20%~80% relative humidity, no condensation
Working power	~110V-240V 50Hz-60Hz
Weight	3.3Kg
Dimension	240*160*205mm (including mesh cover)