



2-channel IP Decoding Card

TV-8002IR-5



Description:

2-channel IP decoding card, with an RJ45 interface, a single card supports up to 4 channels of 4000*3000@25 or 32 channels of 1920*1080@30 or 64 channels of 1280*720@30 decoding. It has work signal indicators, supports IP address modification, and supports board card online upgrade. Through this decoding card, the network data can be directly decoded and displayed on the splicing screen.

RUN: The indicator light flashes when it is running normally.

LINK1: The light remains on.

LINK2: The light remains on.

Feature:

* Video sources: Security IP Camera H.264/H.265/RTSP/RTP: Support mainstream manufacturers IP cameras, such as Hikvision, Dahua, Axis Communications, itarge, Santachi, etc.

* Security media services, support the access of a full range of security equipment from Hikvision, Dahua and Hanbang.

* Coding box, coding card.

Decoding capability:

A single card has 2 RJ45 network ports, each of which has 2 decoding channels. The working mode of each channel can be set independently. The decoding form of each channel in different working modes is as follows:

1 split mode: support a maximum of one 4000*3000@25 signal decoding, support single-screen output.

4 split mode: support a maximum of four 1920*1080@30 signal decoding, support 4-in-1 screen output.

9 split mode: support a maximum of nine 1920*1080@30 signal decoding, support 9-in-1 screen output.

16 split mode: support a maximum of sixteen 1920*1080@30 signal decoding, support 16-in-1 screen output.

The decoding capability of a single network port is: 2 channels of 4000*3000@25 decoding or 16 channels of 1920*1080@30 decoding or 32 channels of 1280*720@30 decoding.

Specification:

Model	TV-8002IR-5
Interface type	Standard RJ45, 10M/100M/1000M adaptive
Interface quantity	Interface * 2
Power consumption	26W
Temperature	0 ~ 50°C (working environment), -55 ~ 70°C (storage environment)
Humidity	10% ~ 80% (working environment), 10% ~ 90% (storage environment)
Board card	Blade card
Weight	0.3 kg
Dimension	203*224*20mm