



HDMI Signal Distributor

TS-9108HS



Description:

A high-quality HDMI distributor with 1-channel HDMI signal input and 8-channel HDMI signals simultaneously output can effectively avoid signal loss during long-distance transmission. It can convert 1-channel HDMI video signal into 8-channel HDMI video signals and display them synchronously through the display terminal.

Feature:

- * Support to divide 1 channel of high-definition video source into 8 channels of high-definition video signal.
- * The high-definition video signal resolution can reach up to 3840* 2160@30Hz .
- * Compatible with HDMI 1.4 standard.
- * 16 EDID working modes for various application environments.
- * Comply with HDCP 1.2 standard-high-bandwidth digital content protection technology.
- * It can automatically identify and configure various display modes.
- * Built-in automatic equalization system, the picture is smooth, clear and stable.
- * Built-in ESD electrostatic protection circuit, all-round system safety protection.
- * Simple and convenient installation, plug and play, no need to set up.

Specification:

Model	TS-9108HS
Protocol	HDMI 1.4, HDCP 1.2
Pixel bandwidth	165MHz, full digital
Interface bandwidth	Total bandwidth 10.2Gbps
Maximum resolution	3840* 2160@30Hz
Interface	HDMI interface
Impedance	100Ω
HDMI maximum input/output distance	Less than 5 meters, at 1920X1080 @ 60Hz while
Power supply	Power adapter: DC 5-15V
Maximum power consumption	5W
Operating temperature	-5°C ~ +70°C
Operating humidity	5% ~ 90%, no condensation
Dimension	257*87*25mm