



Bracket

TS-9500-6U



(Installation rendering)

Feature:

- * It is an accessory used to install the video transmitter on a standard rack. One set of TS-9500-6U can support the installation of eight video transmitters on a standard rack with a height of 6U.
- * The cabinet adopts AC 220V power supply, and the output DC 12V directly supplies power to the transmitter, making wiring very neat.
- * The reasonable ergonomic design makes the installation and removal of the transmitter very convenient.
- * Excellent installation experience, neat and beautiful effect, no more troubles caused by stacking installation and bundled installation.

Compatible Model:

Model	Model	Category
TS-9506KUR	TS-9506KUT	4K UHD video receiver/transmitter for network twisted pair transmission
TS-9506KUR-M	TS-9506KUT-M	
TS-9506HUR	TS-9506HUT	
TS-9506HUR-M	TS-9506HUT-M	
TS-9506KAR	TS-9506KAT	Multi-format HD video receiver/transmitter for network twisted pair transmission
TS-9506KAR-M	TS-9506KAT-M	
TS-9506HCR	TS-9506HCT	
TS-9506HCR-M	TS-9506HCT-M	
TS-9507KUR	TS-9507KUT	Multi-format HD video receiver/transmitter for fiber optic transmission
TS-9507HUR	TS-9507HUT	
TS-9507KAR	TS-9507KAT	
TS-9507HCR	TS-9507HCT	

Specification:

Model	TS-9500-6U
Capacity	8 transmitters
Input power	176V~264VAC, 47/63Hz international adaptive power supply
Output power	DC2.1 (12V 1.5A)×8
Rate power	100W
Dimension	484×153×264mm (L×W×H)
Weight	3Kg
Ambient temperature	-10℃~+45℃
Ambient humidity	10%-80%, no condensation
Device list	6U cabinet×1 Ear accessory×8 Ear screw×16 Standard rack screw×6 DC2.1 power line×8 220V power line×1