



Linear Array Speaker

KA-2800W/KA-2800WS



KA-2800W



KA-2800WS

Feature

- * Clear instructions, user-friendly operation, plug and play, easy to use.
- * Special aluminum alloy hanging parts, simple hanging method, convenient for audio assembly engineering.
- * Powerful design power, making the sound smooth and soft, clear and elastic, with high degree of reduction.
- * Suitable for various industries and occasions such as gymnasiums, multi-purpose conference halls, entertainment industry, etc.
- * With waterproof polyurea spray paint on the surface, it can be used in places with outdoor waterproof requirements.

Specification

KA-2800W

| | |
|----------------------------------|---|
| Model | KA-2800W |
| Speaker type | Two-way linear array full range speaker |
| Rated power | 500W (AES) |
| Peak power | 2000W |
| Nominal impedance | 8Ω |
| Frequency range | 70Hz-20kHz |
| Sensitivity | 100dB (1M/1W) |
| Maximum SPL (nominal/peak) | 128dB/134dB |
| Woofer | 8"×2 |
| Tweeter | 44mm (1.73") compression driver×1 |
| Horizontal coverage angle (-6dB) | 90° |
| Vertical coverage angle (-6dB) | 10° |
| Net weight | 25Kg |
| Dimension (H×D×W) | (300+195)×380×750mm |



Linear Array Speaker

LA-2800W/LA-1800W

KA-2800WS

| | |
|-----------------------------------|---------------|
| Model | KA-2800WS |
| Speaker type | Woofers |
| Rated power | 600W (AES) |
| Peak power | 2400W |
| Nominal impedance | 4Ω |
| Frequency range | 40Hz-400Hz |
| Sensitivity | 100dB (1M/1W) |
| Maximum SPL (nominal/peak) | 127dB/133dB |
| Woofers | 18"×1 |
| Net weight | 38Kg |
| Dimension (H×D×W) | 490×695×505mm |