



Professional Speaker

KP-628S



Description:

It's suitable for various sports venues, theater theaters, auditorium classrooms, banquet halls, outdoor performances, multi-functional halls and various high-end application places.

Feature:

- * The cabinet adopts 18mm birch board CNC cutting technology, unique cabinet structure, internal multi-point ribs are fixed to increase the stability of the cabinet, effectively reduce resonance, and the surface is sprayed with polyurea paint process, which is strong and wear-resistant.
- * One-piece stamping and forming rigid protective mesh grille, with acoustic high sound-transmitting cotton mesh, to protect the speaker and increase the service life;
- * Equipped with 2 18-inch ferrite subwoofer units, inverted cabinet design, the low frequency can be extended to 40Hz, releasing a thick and powerful low frequency effect, providing solid and powerful low frequency energy, meeting various sound reinforcement environments and application requirements.
- * Professional speaker socket plug with good electrical characteristics.

Specification:

Model	KP-628S
Impedance	4Ω
Frequency response	40Hz-400Hz
Rated power	1200W
Peak power	4800W
Sensitivity	101dB/W/M
Max SPL(rated/peak)	132dB/138dB
Woofers	18" woofer ×2
Dimension	560×1068×761(mm) (H× W×D)
Weight	83Kg