



Ceiling Speaker

TS-206DT



Feature:

* The speaker adopts POE power supply, Dante-to-analog signal output, built-in DSP processing function, and full network digital amplifier modules. It supports visualized adjustment through PC software and meets different demands of sound quality. Audio transmission with Dante network protocol has the characteristics of avoiding interference from transmission lines, high fidelity, and no delay. The network transmission and simple engineering wiring can make the installation of amplifiers and speakers more convenient, safe and reliable.

* PoE power supply: support IEEE802.3af/at/bt standards respectively.

* DSP processing functions: save scene, import scene, export scene, reset, 5-band equalizer, high-pass filter, low-pass filter, treble enhancement, bass enhancement, limiter, gain, etc.

* High-grade flame-retardant plastic back cover.

* High-end coaxial speaker composed of a 6.5-inch mid-woofer and a silk-film neodymium magnetic tweeter.

* The input interface adopts 10/100MRJ45, 1 audio channel Dante input. It must support POE power supply, and the POE is compatible with 802.af/at/bt standards. It uses CAT5 cables or better network cables.

* Widely used in hotels, shopping halls, supermarkets, schools, entertainment places, etc.

Specification:

Model	TS-206DT
Input interface	The input interface adopts 10/100MRJ45, 1 audio channel Dante input. It must support POE power supply, and the POE is compatible with 802.af/at/bt standards. It uses CAT5 cables or better network cables.
Output power	Peak power: 100W; rated power: 60W
Sensitivity	0dBfs
Frequency response	90Hz-20KHz
THD+N	<0.3%
SNR	>90dB
Speaker	6.5-inch mid-woofer + 1-inch silk film tweeter coaxial speaker
Opening size	250mm
Product size	190×280×280mm (H×W×D)
Weight	2.47kg