



## Column Speaker

### TS-603C/TS-803C/TS-1203C



## Feature

- \* Adopt six 3-inch full range speaker units.
- \* The cabinet adopts 12mm high-quality high-density board, precise CNC processing, wear-resistant spray paint treatment.
- \* Accurately designed speaker frequency response can optimize high fidelity reduction of the vocal.
- \* Spliced array design achieves a wider sound field coverage with fewer speakers.
- \* It is suitable for large multipurpose halls, theaters, stadiums, outdoor performances, etc.

## Specification

Model	TS-603C	TS-803C	TS-1203C
Rated power	200W	300W	400W
Peak power	800W	1200W	1600W
Max SPL (rated/peak)	118dB/124dB	120dB/126dB	124dB/130dB
Nominal impedance	6Ω	4Ω	6Ω
Frequency range	80Hz-20kHz	70Hz-20kHz	60Hz-20kHz
Sensitivity	95dB(1M/1W)	95dB(1M/1W)	98dB(1M/1W)
Speaker unit	3" ×6	3" ×8	3" ×12
Horizontal coverage angle	110°	110°	110°
Vertical coverage angle	100°	100°	100°
Net weight	9.8kg	12.9kg	20.24kg
Dimension	760×150×195mm(H×W×D)	970×150×195mm (H×W×D)	1500×150×195mm (H×W×D)