





Professional Active Speaker (Built-in DANTE)

TS-610DT



Description:

It works with the DANTE audio processor to form a set of high-end entertainment and conference professional sound system with outstanding vocal performance. It is suitable for various high-end conference rooms and multi-function halls as the main speaker or auxiliary speaker.

Feature:

- * Adopt a 10" mid-woofer and a 1.4" compressed tweeter.
- * 15mm plywood housing, light weight, wear-resistant spray paint treatment and dust-proof net cotton inside.
- * The frequency divider in precise design optimizes the vocal MF performance.
- * Built-in DANTE function of dual network ports can realize hand-in-hand connection.
- * Support high-quality and long-distance signal transmission.
- * The entire series is equipped with efficient high-power amplifier modules and powerful audio processors. Through different applications of the DANTE audio processor supporting system, it supports comprehensive parameter settings, including parameter equalization, frequency division, delay, and limit.
- * Multiple screw hoisting holes, a pole socket with a diameter of 35mm, various installation methods.

Specification:

Model	TS-610DT
Impedance	8Ω
Frequency response	55Hz-20KHz
Rated power	300W
Peak power	1000W
Sensitivity	98dB/W/M
Maximum SPL(rated/peak)	123dB/128dB
Coverage angle	(H)80°(V)60°
Tweeter	1.4" compressed tweeter ×1
Woofers	10" woofer ×1
Line input sensitivity	0dB
Network port	DANTE protocol
Bandwidth	1000M
Dimension	510×325×300mm (H×W×D)
Weight	19Kg
Power supply	AC 220V 50Hz
Power consumption	240W