



Professional Speaker

TS-610T/TS-612T/TS-615T



Description

It works with the professional amplifiers and audio processors. It can be used as a monitor speaker in large conference halls and multipurpose halls, etc.

Feature

- * Adopt a mid-woofer and an annular polyethylene diaphragm compressed tweeter.
- * 15mm plywood housing, light weight, wear-resistant spray paint treatment, external hard hexagonal iron mesh, and dust-proof cotton inside.
- * The frequency divider in precise design optimizes the vocal MF performance.
- * The cabinet has a polygonal structure, and the monitoring angle can be adjusted according to different venues.

Specification:

Model	TS-610T	TS-612T	TS-615T
Impedance	8Ω	8Ω	8Ω
Frequency response	60Hz-20KHz	50Hz-20KHz	45Hz-20KHz
Rated power	300W	400W	500W
Peak power	1200W	1600W	2000W
Sensitivity	98dB/W/M	99dB/W/M	100dB/W/M
Max SPL(rated/peak)	123dB/129dB	125dB/131dB	127dB/133dB
Coverage angle	(H)80° (V)60°	(H)80° (V)60°	(H)90° (V)70°
Tweeter	1.4" compressed tweeter ×1	1.7" compressed tweeter ×1	1.7" compressed tweeter ×1
Woofer	10" woofer ×1	12" woofer ×1	15" woofer ×1
Dimension (H×W×D)	340×510×380mm	380×585×440mm	395×690×465mm
Weight	17.5Kg	20.5Kg	26.5Kg