



Description

It is suitable for multimedia classrooms, general classrooms, conference rooms, training rooms, specialty stores and other places on demand of reinforcement.

Feature

- * Support 1 channel microphone, 1 channel stereo line input, 1 channel stereo line output.
- * Output overload, overvoltage, short circuit protection.
- * With mute function, the microphone has priority over the line input.
- * 1 microphone volume adjustment, 1 line input volume adjustment, 2 treble and bass adjustment.
- * Adopt 1 4-inch woofer unit and a 2.5-inch tweeter unit.
- * With 100V broadcast input interface prior to local broadcast.

Specification

| | |
|-----------------------|--|
| Rated output power | 2×12W (including main box and auxiliary box) |
| Output impedance | 4-8Ω |
| Input sensitivity | AUX IN : 350mV±20mV/10KΩ ; MIC : 5mV±0.5mV |
| SNR | ≥70dB |
| Frequency response | 80~20KHz(±3dB) |
| Line out | 1V |
| Volume adjustment | 1 MIC volume, 1 AUX volume |
| THD | ≤1% |
| Operating temperature | 5°C ~ 40°C |
| Working humidity | 20%~80% relative humidity, no condensation |
| Power consumption | ≤30W |
| Supply voltage | ~220V 50Hz , DC 24V 2A |
| Dimensions (W×H×D) | 289*146*100 mm |
| Weight | 2.6kg |