



Description:

Applied to outdoor and indoor fixed installation background sound reinforcement, theme parks, scenic spots and other cultural and tourism sound reinforcement application places.

Feature

- * Composed of a 5-inch subwoofer unit and a 1-inch dome tweeter.
- * Designed with ABS+PC injection molding, suitable for all-weather use.
- * Equipped with an aluminum mesh grille and an acoustic sound-permeable sponge inside to prevent dust and water droplets from damaging the speaker unit.
- * Precise two-way crossover design is adopted to optimize the frequency response and the mid-range expressiveness of the vocal part.
- * With constant resistance and constant voltage selection function. With a U-shaped bracket, it is convenient for engineering installation.

Specification

Model	TW-775K
Speaker type	Plastic wall mounted speaker
Rated power (100V)	5W/10W/20W/40W/constant resistance 8Ω, 40W
Rated power (70V)	5W/10W/20W/40W/constant resistance 8Ω, 40W
Nominal impedance	2000Ω/1000Ω/500Ω/250Ω/122Ω constant resistance 8Ω
Frequency range (-10dB)	80Hz-20kHz
Sensitivity (1M/1W)	90dB±3dB
Maximum SPL	109dB
Coverage angle (-6dB)	100°(H)×80°(V)
Subwoofer	5-inch subwoofer×1
Tweeter	1-inch tweeter×1
Net weight	3.3kg
Dimension (H×W×D)	278×170×172mm