



# Microphone

## TV-63



(Used with TV-S63WL, cannot be used alone)

### Feature:

- \* Adopt an integrated design and simple structure, built-in 1 digital microphone, 360° omnidirectional pickup, and the maximum pickup distance reaches 5 meters.
- \* One-key mute switch with clear LED status indicator.

### Voice characteristics

- \* Full duplex echo cancellation depth:  $\geq 65\text{dB}$ .
- \* Full duplex echo cancellation time: 500ms.
- \* Two-way noise compression:  $\geq 18\text{dB}$ .
- \* Line echo cancellation depth:  $\geq 25\text{dB}$ .
- \* Line echo cancellation time: 32ms.

### Audio characteristics

- \* Microphone frequency response: 100Hz-20KHz.
- \* Microphone pickup range:  $\geq 5$  meters.
- \* Microphone pickup angle: 360 degrees.
- \* Microphone quantity: 1.

### Interface characteristics

- \* Microphone interface: RJ9 interface  $\times 1$ .

### Electrical characteristics

- \* Power supply: main microphone power supply.

### Working environment

- \* Reverberation time:  $< 0.5\text{S}$ .
- \* Noise level:  $< -48\text{ dBA}$ .

### Physical characteristics

- \* Housing: black.
- \* Working temperature:  $0^{\circ}\text{C} \sim 50^{\circ}\text{C}$ .
- \* Working humidity: 20% -85%.
- \* Dimension(  $\phi$  ): 10.0 $\times$ 4.0cm.
- \* Weight: 1kg.