




Hd Video Conference Terminal NT90MB Series

Product Optional Specifications:MB01M4

Embedded software: HD video conferencing with MCU terminal embedded software V2.3



Description

* NT90MB series is a new split-type HD video conference terminal, which supports H.265 technology, ultra-low bandwidth to fulfill 4K video effects , integrated with various audio and video interfaces, suitable for various medium and small size of meetings.

Features

- * Adopt split type structure, built-in hardware video processing unit,with embedded operating system, non-Windows or Android operating system.
- * Support ITU-T H.323 standard protocol, with good compatibility; support VCS protocol, H.239 dual-stream protocol, both main and auxiliary streams can reach 1080P.
- * Call bandwidth supports 64Kbps-8Mbps; support QCIF, CIF, 4CIF, 480P, D1, 720P, 1080P, 4K video resolution.
- * Support 1280*720P 60fps/50fps/30fps/25fps □ 1920*1080P 60fps/50fps/30fps/25fps HD video signal input;
- * Support 1280 * 720P 60fps / 50fps / 30fps / 25fps, 1920 * 1080P 60fps / 50fps / 30fps / 25fps, 3840 * 2160P HD output.
- * Support H.264, H.264 MP, H.264 HP, H.265 video codec protocol, support G.711, G.722, G.722.1, G.722.1C, OPUS and other audio codec protocols, the highest sound quality Up to 48KHz.
- * The built-in MCU function module supports the holding of 4-party meetings, and the built-in MCU function supports the smooth expansion to 22 points; Support built-in MCU conference to hold mainstream auxiliary conference, support PC version or mobile terminal to join the conference.
- * Support the interception of auxiliary stream screen for labeling function, and meet the interactive operation of remote training and teaching.
- * Support through 2.4G remote control, web, touch, mouse and keyboard to control the terminal, support remote control flying mouse control mode.
- * Support remotely open and close remote video, support flying mouse mode to drag and change the video position in the screen layout.
- * The terminal adopts the B/S management structure and Can be remotely managed by logging in to the web via a browser.
- * Support the chairman control mode. If getting the chairman's right, the parameters such as the encoding rate and resolution of the dual-stream dual-stream can be controlled. The PTZ camera can be moved up, down, left, and right, and zoomed and zoomed.
- * Support active opening of the remote auxiliary stream screen, and can view auxiliary stream pictures of up to 25 different video terminals at the same time.
- * Support single-screen dual-display, dual-screen dual-display application functions, multi-screen layout, picture-in-picture and other common layout types, single-screen support 25-channel display at the same time.
- * You can control the bandwidth of the dual-stream at the remote site and perform PTZ control on the remote site.
- * Support controlling the spoken right of other terminals in the same conference.
- * Equipped with USB interface, support USB storage device; support conference recording function, can directly record video and audio during the conference.
- * The terminal has built-in conferences sign-in, electronic whiteboard, electronic voting, file sharing and other data conferencing functions to meet the needs of remote training, teaching and other scenarios.
- * The terminal can be provided with a complete SDK development manual, which can be used to adjust the camera, send scroll messages, set banners, switch screen layout, and control the floor rights of each site through the SDK,the third-party system can be seamlessly integrated.
- * It has rich audio and video interface: support 1 channel USB3.0 high-definition video input interface, 2-channel HDMI high-definition input interface,2-channel HDMI high-definition output interface; 2-channel audio input interface, 1 independent audio output interfaces, can be connected to speakers or mixer.
- * Support the self-repair function in case of IP network packet loss, to ensure that there is no mosaic when the packet loss rate reaches 5%. The conference can still be held normally when the packet loss rate reaches 8%. The image to be acceptable when it is 20% packet loss . Audio is not affected and the conference is guaranteed to proceed normally with 70% packet loss rate.
- * With ultra strong network adaptability, it adjusts the resolution according to the network automatically to ensure the meeting goes fluently.
- * Support for banner, add banners to meeting screens, and set whether to enable banner and banner font size, font color, background color, and transparency.
- * Support for scrolling messages, send scrolling messages, and set whether to enable scrolling and scrolling message font size, font color, background color, transparency, and number of scrolls.
- * Support automatic noise suppression, automatic gain control and automatic echo cancellation, lip sync and other audio processing functions.
- * Support the site mute and silence function, and the volume of venue sound is adjustable.
- * Support voice priority, QOS policy mode, IP Precedence, Diffserv.
- * Support IPV4 and IPV6 protocols, support NAT traversal, and have the ability to cross routers and firewalls to ensure system security.
- * It is with Excellent management and maintainability, support local audio and video loop diagnostics; one-button local audio and video testing; support for network ping test, call log and history query on the operation interface.

Model	MB01M4
Mcu Build-in Mcu	4 sites
Framework Protocol	In accordance with ITU H.323 and VCS protocol
Video Input	3-channel HD video input interface, USB3.0*1、HDMI*2
Video Output	2-channel HD video output interface, HDMI*2
Audio Input	2-channel audio input interface, MIC IN*1、LINE IN*1
Audio Output	2-channel audio output interface, HDMI*1、LINE OUT*1
Internet Port	1-channel Gigabit Ethernet port, RJ45*1
Usb Interface	2 USB2.0 ports for connection to expansion devices or online upgrades
Video Protocol	Support H.264, H264HP, H264SVC, H.265 video standard protocol
Dual Stream Protocol	Support H.239 dual stream protocol
Display Method	Support 4:3 and 16:9
Ambient Temperature	0°C to 35°C (operating state) -40°C to 55°C (non-operating state)
Relative Humidity	10%~80% (operating status) 0%~95% (non-operating state) (non-condensing)
Size	220mm×210mm×30mm
Power Supply	DC 12V