




# HD Integrated Terminal

## Embedded software: VMS visual management system terminal V2.0 TV-711A



### Description

It is an integrated input and output terminal of a visual management platform. It integrates powerful system functions such as visual management, KVM collaboration, splicing, network transmission, matrix, central control and fusion. It adopts a completely distributed structure design and supports unlimited unit extension; any unit failure will not affect the operation of the entire system, featuring high reliability. It is designed with a redundancy and backup design, bringing strong stability; it supports KVM cross-screen roaming, and mouse control with ultra-low delay. With built-in self-developed video splicing synchronization algorithm, it can be directly connected to the LED video wall. It is characterized by desktop design (optional rack accessories) and elegant appearance.

### Feature

- \* The integrated input and output design can be freely configured as input terminal, output terminal, KVM input terminal or KVM output terminal.
- \* When used as an input node, it supports 1920\*1080P@60fps, 1920\*1080P@30fps high-definition video signal input and backward compatibility and multiple streams are transmitted simultaneously, when used as an output node, it supports 1920\*1080P@60fps, 1920\*1080P@30fps high-definition output and backward compatibility, and transmit multiple streams at the same time.
- \* When used as an input node, it supports 4-channel 1080P@60fps or 8-channel 1080P@30fps H264/H265 decoding display, support screen tiling, scaling, overlaying, splitting, and roaming.
- \* Supports real-time preview of the input signal through the client, and the signal status is under control.
- \* Station logo: When used as an input node, it supports adding text or picture to the input source as the logo without adding external devices; the font, font size, color and background color of the logo can be customized; the logo size can be changed as needed.
- \* Subtitles: When used as an output node, subtitles (such as welcome messages) can be displayed on the splicing screen without adding external devices. The font type, size, color, and position can be customized, and dynamic scrolling subtitles is supported.
- \* Input box subtitles: When used as an input node, it supports displaying subtitles on the input source without adding external devices. You can set the font type, font size, font color, background color, transparency, display position, etc.
- \* Local HD basemap: without adding external devices, it supports the display wall basemap function; you can load local pictures, and can set the basemap function on and off on the software.
- \* With 3.5mm analog audio interface and HDM digital audio interface, it supports the transmission of original PCM audio without coding compression;
- \* Supports KVM function, capture screen and send screen graphically (non-text), send screen to any monitor or large screen, support KVM cross-screen roaming, support virtual mouse control to optimize KVM operation experience, support cross-platform operation, including Windows, Linux, Mac and other system platforms.
- \* KVM supports OSD menu visual management, the number of preview videos on a single page can be adjusted as needed, the maximum number of previews on a single page can reach 8, and information prompts and confirmations are provided meanwhile.
- \* Supports KVM role permission management, control KVM signal management permission through the server permission management function.
- \* Supports access to fingerprint sensor to realize KVM fingerprint identification login, and support to cooperate with USB camera to realize KVM face recognition login function, and establish a fast, reliable and safe access channel.
- \* Built-in self-developed video splicing synchronization algorithm, no splicing processor is required, it can be directly connected to LED sending card, LCD, DLP and other splicing screens, and the picture is synced without tearing.
- \* Built-in input synchronization function, supports 4 input nodes for synchronous acquisition and synchronous encoding of a 4K signal source, and transmits to 4 output nodes for synchronous decoding and synchronous display, the whole 4K signal picture is clear and smooth, without tearing, realizing 1:1 wall display of 4K signal source.
- \* Supports the function of central control, with independent RS-232 serial port, RS-485 interface, 2 RELAY ports, 3 IO ports and 4 infrared output interfaces, and support custom programming.
- \* Built-in infrared learning module, support learning infrared codes of infrared remote control devices including camera remote control.
- \* The control interface supports two-way data transmission, and supports access to sensor devices to display environmental data and other information on the tablet side.
- \* With a 2.23-inch OLED display, it can display the terminal IP address and operating status in real time.
- \* Desktop structure design, optional cabinet-type cooling rack, and unified power supply management.



# HD Integrated Terminal

## Embedded software: VMS visual management system terminal V3.031 TV-711A

- \* Using domestic chips and domestically controlled embedded Linux system, supporting 7x24 hours of continuous operation;
- \* Supports online batch upgrade through the server.
- \* Supports automatic recovery from abnormal power failure, and the device automatically restores to the previous status.
- \* Supports one-key reset dynamic IP, one-key reset and restore file system functions.
- \* Supports POE, adapter dual power supply, low power consumption, maximum 12W.
- \* Supports fiber/network port dual link backup. When any link fails, it supports automatic seamless switching to another link for transmission, and no packet loss occurs during the switching process.
- \* Support network packet loss repair mechanism, when 10% network packet loss, the audio and video is clear and smooth, without freeze or mosaic.
- \* The terminal node supports the offline maintenance function. When disconnected from the server, the original display screen can still be displayed and output normally, without screen freeze or blackout.
- \* Supports national secret algorithms SM2, SM3, SM4 to encrypt and transmit signaling and media streams to ensure data security and controllability.
- \* Supports the push function of visual video wall, which can display the video wall image in real time, adjust the screen layout of any video wall, the splicing mode of signal source, and control the zoom in, zoom out, and movement of signal source.
- \* Supports to take over 8 1080P30 video signals at the same time, all 8 video signals support KVM control, it supports one-key full-screen zooming in on any signal source, one-key restoration of the full-screen signal source image, and one-key push of any video signal currently taken over to be displayed on any window of any video wall.
- \* When used as an output node, it can be used with the input node to realize the USB transparent transmission function, no need to add additional equipment, no need to use a separate network, and only need to connect a network cable or two-way optical fiber cable to realize the common transmission of media, signaling, and USB transparent transmission data;
- \* Supports SIP protocol, built-in seat video intercom function, can connect external USB camera, USB headset and standard SIP protocol equipment for video intercom.
- \* When used as an output node, it supports setting the audio equalizer, enabling or disabling the equalizer, enabling or disabling dynamic compression, and built-in 18 commonly used equalizer scenes, which can be switched with one key or fully customized, for 60 Hz, 170 Hz, 310 Hz, 600 Hz, 1K Hz, 3K Hz, 6K Hz, 12K Hz, 14K Hz, 16K Hz and other audio frequency bands, the gain can be controlled independently, and the range is -20dB to 20dB.
- \* Supports signal cropping function, you can set cropping coordinates, cropping width and height to crop the input signal.
- \* Supports signal source annotation function. When used as an input node, you can annotate the input signal through the control tablet, PC client, KVM seat, and web terminal. It supports free drawing, straight line, arrow, square, circle, triangle and other annotation forms. You can set the thickness and color of the annotation line, undo or restore the annotation operation, and delete the annotation or delete all by selecting the eraser.
- \* Supports KVM instant communication function, you can communicate with a single person or all members through text or screenshots, and the picture supports zooming in and out. After zooming in, you can drag and view it.
- \* Supports adding time display control, you can set the coordinate position, font size, font color, background color, transparency, font spacing, font type, display style, etc. of the time display.
- \* Supports adding temperature display control, you can set the coordinate position, font size, font color, background color, transparency, font spacing, font type, temperature prefix, temperature suffix, etc. of the temperature display.
- \* Supports adding humidity display controls, and can set the coordinate position, font size, font color, background color, transparency, font spacing, font type, humidity prefix, humidity suffix, etc. of humidity display.
- \* Supports adding real-time people counting controls, and can set the coordinate position, font size, font color, background color, transparency, font spacing, font type, statistical prefix, statistical suffix, etc. of statistical display.
- \* Supports KVM account following function, after logging into any KVM wall, automatically open the window to display the signal source used last time.
- \* Supports setting the wall window layout to 1P, 4P, 9P, 1+4P, 1+5P, 1+7P, 2+8P, 1+12P, 16P and other common layouts, and can also customize the number of rows and columns of the wall layout, support using the original layout of the wall output box, and can turn on the automatic fill layout mode.
- \* Supports OCR text recognition function, which can capture a computer screen captured by the input box as a picture for AI analysis, extract the text in the picture and transfer it to another computer through the KVM output box, and the extracted text can be pasted into a file.



# HD Integrated Terminal

## Embedded software: VMS visual management system terminal V3.031 TV-711A

### Specification

<b>Model</b>	TV-711A
<b>Processing capability</b>	When used as an input node, it supports 1920*1080P@60fps, 1920*1080P@30fps high-definition video signal input and is backward compatible; when used as an output node, it supports 1920*1080P@60fps, 1920*1080P@30fps high-definition output and is backward compatible. Support 8-channel 1920*1080@30fps codec.
<b>Codec capability</b>	Support H.264/H.265 video encoding, PCM audio lossless transmission
<b>Video port</b>	1*HDMI IN (support audio), 1*HDMI OUT (support audio), 1*VGA OUT
<b>Audio port</b>	1*3.5mm stereo input, 1*3.5mm stereo output, input sensitivity: 775mV
<b>USB Network port</b>	2*USB2.0 (KVM interface), 1*USB3.0 (support audio and video input)
<b>OPTICAL port</b>	1*RJ45, 10/100/1000Base-T, support POE
<b>Serial port</b>	1*SFP
<b>I/O port</b>	3*I/O port
<b>Infrared port</b>	1*IR learning window, 4*IR OUT
<b>Weak relay port</b>	2*RELAY port
<b>Reset button</b>	1*pinhole RESET button
<b>Mode switch</b>	1*input and output mode switch
<b>Display screen</b>	2.23-inch OLED display with 128*32 pixels
<b>Power supply</b>	DC 12V/POE
<b>Max power consumption</b>	12W
<b>Ambient temperature</b>	-10°C~45°C (working state); -15°C~45°C (non-working state)
<b>Ambient humidity</b>	5%~90% (working state), no condensation
<b>Weight</b>	About 0.9kg
<b>Dimension (L*W*H)</b>	240*117*44.8mm