



# Cloud Conference Server

## TR-0600T



### Description:

The conference management server is a high-performance server specially used for conference systems. Working with system software, it can realize conference appointment, sign-in, voting, conference room management and other functions.

### Feature:

- \* High-quality 1.0mm galvanized steel plate, stable structure, double-ball high-speed fan, excellent heat dissipation.
- \* 1U rack-mounted design, stable structure and excellent heat dissipation.
- \* Support hot swap, support up to 4 hard drives, support RAID0, 1, 5, 10.
- \* Dedicated remote port supports remote management.
- \* 2 Gigabit Ethernet ports, support port aggregation function.
- \* Dedicated server power supply, support redundant power supply.

### Specification:

<b>Model</b>	TR-0600T
<b>GPU</b>	Integrated display CPU latest graphics processing core
<b>Processor</b>	E3-v5 quad core processor
<b>RAM</b>	Standard 8G ECC DDR4 2400, support maximum 64G ECC DDR4 (4 slots)
<b>BIOS</b>	128Mb SPI Flash EEPROM with AMI BIOS
<b>Onboard LAN</b>	2 10/100/1000M bps network ports support port aggregation
<b>Remote control</b>	1 RTL8201N dedicated remote interface, support intelligent platform management interface; support virtual media and KVM
<b>IDE controller</b>	4xSATAIII (support hot swap)
<b>RAID</b>	Support RAID 0, 1, 5, 10
<b>I/O interface</b>	2xUSB3.0,Front 2xUSB2.0, rear 2xUSB2.0, 1xVGA, 1*IPMI independent remote management port; 1*RS232 COM port
<b>Hardware monitoring</b>	Fault/Error/Overload and Alarm (including Disk/RAID/Power/Fan/Temp/IO performance)
<b>Hard disk</b>	2T (3.5 inch) mechanical enterprise hard drive
<b>Box qty</b>	The 4 hard disk extraction boxes are equipped with locking devices, and the sliding rail design makes the hard disk extraction more convenient
<b>Hard drive hot swap</b>	Support hard disk hot swap
<b>Power</b>	250W
<b>Working voltage</b>	AC 100-240V, 50/60Hz
<b>MTBF</b>	50000/H (MTBF)
<b>Working temperature</b>	-10°C~60°C
<b>Relative humidity</b>	5%-90%, no condensation
<b>Dimension</b>	650×437×44.5mm (D×W×H), with guide rails on both sides of the case