



Description

The fiber matrix command and dispatch platform, working with the management software, integrates application functions such as KVM seating management, large-screen display management, IoT device control, audio control, and video recording management.

Feature

- * 1U rack-mounted, stable structure, silver-white casing, fine craftsmanship, stylish appearance
- * Pure industrial design, excellent heat dissipation structure, the chassis has four built-in 40 double ball high-speed fans, the chassis can resist contact 4KV strong electromagnetic interference; 1U server power supply, AC100-240V input
- * High-performance processor, Intel® Xeon® processor E3-1200 v3/v4 series processor
- * Rich interfaces, supports remote management, supports hot swapping, supports up to 4 hard drives, comes standard with 4 hard drive boxes, is compatible with 3.5 and 2.5-inch hard drives, and supports RAID array cards

Specification

Processor	E3-V5 processor
BIOS	128Mb SPI Flash
Memory	8G DDR4
Network	2*10/100/1000Mbps adaptive network port
Remote control	Support remote wake-up, 1*remote IPMI management port
Hard disk space	Comes standard with 4 hard drive boxes, compatible with 3.5 and 2.5-inch hard drives, supports Raid 0 1 5 10,
Harddisk	1T (3.5-inch) mechanical enterprise-class hard drive + 128G (2.5-inch) SSD
Hard drive hot-swappable	support
Interface	2*USB3.0, 4*USB2.0 (2 front, 2 rear), 1* VGA, 2*LAN, support 10/100/1000Mbps, 1*IPMI independent remote management port, 1*RS232 COM mouth
Function	Built-in operation guide of the non-sensory dispatching system
Operating temperature	-10°C-60°C, 5% ~ 95% (non-condensing state)
Storage temperature	-20°C-60°C, 5% ~ 95% (non-condensing state)
Power supply	AC100-240V
Installation method	On-shelf type
Operating system	Pre-installed Windows Server 2016 (not activated at the factory)
Overall dimensions (W*H*D)	660 * 43.5 * 430 (mm)
Weight	11.35kg