



## SP2 (VA-6506) Ceiling Speaker



### Features:

- \*High-quality ceiling speaker, full-frequency speaker design, iron flame retardant protective speaker rear cover. Spring presser foot system is convenient for users to install. Suitable for shopping malls, supermarkets, hotels, etc.
- \*Adopt embedded computer technology and DSP audio processing technology.
- \*Built-in 2-channel network hardware audio decoding module supports TCP/IP and UDP protocols to realize network transmission of audio signals.
- \*POE (IEEE 802.3 at) power supply mode is supported. And only one network cable is needed to connect to POE switcher, so the construction is simple and convenient, and the maximum connection distance can reach 80 meters.
- \*Equipped with DC 24V standby power interface, it is suitable for providing power when the power demand is greater than 10W or for non-POE network.
- \*The digital amplifier with intelligent gain adjustment, adaptive power supply and automatic power adjustment is always in the working state of optimal performance and maximum efficiency.

### Specification:

Model	VA-6506
Network interface	Standard RJ45
Protocol	TCP/IP, UDP
Audio format	MP3
Speaker load	10W
Rated power	16W
Power supply mode	POE (IEEE 802.3 at)/DC 24V 1.5 A
Sensitivity	88dB
Frequency response	110-15KHz
Speaker unit	5" x 1
Cutout size	170mm
Size	200 x 100 mm
Weight	1Kg