



# Speaker VA-6506

(Specification: SP42R)



## Application

1. Public broadcasting for airports, automobiles, railways and subway stations.
2. Internal broadcasting for ships and warships.
3. Public and emergency broadcasting for schools, shopping malls, hotels, and institutions.
4. Emergency broadcasting in public places such as parks and squares.

## Feature

- \* Aluminum alloy main integrated structure + sandwich structure of front and rear mesh covers, high strength, firm and reliable.
- \* Ultra-thin body shape, the total thickness is not more than 40mm, the surface is anodized with fine sand grains, beautiful and generous.
- \* Built-in 2 planar drivers, front and rear 360-degree sound, plane wave transmission, long transmission distance.
- \* Support 4Ω 50W power output.
- \* Support direct connection with conventional fixed-resistance power amplifiers for public address sound reinforcement.
- \* Multi-point installation, horizontal or vertical installation.
- \* Anti-mildew, anti-moisture, anti-salt spray.

## Specification

Rated power	50W
Input interface	2 core waterproof aviation socket
Frequency response	80 Hz -18KHz
Impedance	88dB±3dB
Sensitivity	98dB ( MAX )
Sound pressure level	2 sets
Number of drives	Front and rear
Voice direction	536.5×345×40mm
Dimensions	About 3.15Kg
Net weight	-25°C~60°C
Operating temperature	Hoisting, Horizontal