



Touch Terminal

VA-6507 (Specification: RC21)



Description

The IP touch screen terminal is the remote broadcast on-demand panel of PA system, which can realize the free on-demand function. The on-demand unit can display the catalog through the touch screen, and supports list playback, loop playback, random playback, pause/play, previous/next son, etc.

Feature

- * With 1 RS485 interface to connect to the PA system for remote control;
- * Support the installation of standard 86 bottom box;
- * With 4.0-inch capacitive interactive touch screen, support catalog display of broadcast background music, list playback, loop playback, random playback, pause/play, previous/next son and other operations.

Specification

Voltage	5-36V (error $\pm 0.2V$)
Power consumption	Sleep: 0.3W; Darkest: 1.5W; Brightest: 2.4W
Communication method	Rs485
Communication baud rate	RS485: 1200~115200bps, typical baud rate: 9600bps
Communication connector specification	2EDG3.81-4P and RJ45 Ethernet socket
Picture download	SD card
Effective display area (AA)	Length x width = 71.9mm x 70.2mm
Product size (L x W x H)	90.7mm x 90.7mm x 27.9mm
Display size	4.0 inches
Resolution	480*480
Display type	TFT LCD screen
Backlight tube	LED
Brightness (cd/m ²)	250
Backlight life (h)	>20,000
Contrast	800:1
Viewing angle (L/R/T/B)	80/80/80/80
Touch type	Capacitive touch screen
Touch method	Single point, slide touch
Transmittance	90% above
Operating temperature	-20~+70°C
Storage temperature	-30~+80°C
Installation direction	Support 0, 90, 180 and 270 degree rotation installation display