



Description

The rental LED video wall business is one of the service industries that have developed vigorously in recent years. The LED video wall is widely used in the stage or background of important events such as TV studios, large-scale performance activities, opening ceremonies of important events, sports competitions, and corporate celebrations. The texts, pictures and videos played on the LED video wall together create a colorful atmosphere, which greatly improves the level of the activity.

Feature

- *With fast installation design. The installation and dis-assembly of the screen can be completed in a short time.
- *Support the arbitrary direction of the signal line, and meet the different arrangement and placement of cabinets, create pictures with different effects.
- *With arc lock -6° , -3° , 0° , $+3^{\circ}$, $+6^{\circ}$ arc shape.
- *Support 256-level brightness adjustment and white balance custom adjustment.
- *Adopt signal folding technology, unit modules do not need to be cascaded, which greatly improves the display performance of the product.
- *Adopt large modules, with only 4 modules per cabinet, which reduces internal connections and improves product stability.
- *The back cover adopts a U-shaped push-lock design, and the power supply and receiving card can be maintained and replaced without dismantling any components.
- *High-end constant current drive chip with built-in PWM can realize high refresh rate, high grayscale high refresh rate, high grayscale 65536 grayscale products. The picture is stable, which can easily meet the requirements of high-end applications such as stage performances and broadcasting.
- *The new structure design meets the requirements of hoisting and stacking installation, as well as indoor and outdoor requirements. The cabinet design is suitable for multiple pitches of Led screen.
- *The new structural design meets the requirements of hoisting and stacking. The cabinet is simplified and compatible with various pitches.
- *High grayscale and high refresh rate: gray scale 12/14/16 bit, refresh frequency $>7680\text{Hz}$;
- *Optimize heat dissipation design through PCB circuit, don't need external fans, air conditioners, etc., low noise; light weight of the cabinet, low installation cost; low power consumption of the cabinet, saving operating costs.
- *Equipped with various specifications of the flight cases, which is convenient for storage and transportation of the cabinets, and has a good protective effect on the LED video wall.
- *Support DCI-P3 (98%) color gamut requirements, support BT.2020, DCI.P3, BT.709, sRGB and other color gamut conversions, support X, Y, Z and Y, U, V color conversion.



Outdoor Full Color LED Video Wall

TV-PH260-YD

Specification

Model specification	
LED encapsulation	SMD1515 black light
Pixel pitch	2.604mm
Resolution	147456 pixels/m ²
Lamp bead/IC	XR special lamp bead/Aggregate MBI5264IC
Pixel composition	1R1G1B
Module resolution	96*96
Module dimension(mm)	250*250
Cabinet resolution	192*192
Cabinet dimension (mm)	500*500
Cabinet weight	9Kg/pc
Operating voltage	DC+4.2V~+5V
Main specification	
Best view distance	≥7.8m
Horizontal view angle	≥175°
Vertical view angle	≥175°
Maintenance method	Front /Rear maintenance
Control method	Synchronous control
Drive device	Constant current
Refresh rate	≥7680Hz
Frame rate	60/120/160/180/240Hz
Scanning method	14S
Brightness	200-2000CD/m ²
Grayscale	12/14/16bit
Contrast	≥20000:1
Attenuation rate (after 3-year work)	≤15%
Brightness adjustment method	Automatic / manual: 1-100%
MTBF	≥20000H
Lifespan	≥100000H
Failed rate	≤1/10000 and no continuous failed pixels
Software	Professional LED video wall programming software
Storage temperature	-35°C~+85°C
Operating temperature	- 20°C~+40°C
Operating voltage(AC)	90V-270V(50Hz/60Hz)
Average power consumption	≤307W/m ²
Maximum power consumption	≤920W/m ²
Cabinet specification	Die-casting aluminum cabinet
Brightness uniformity	≥98%
IP level	IP5X