



# LED Windowsill Light

## TL-LH5203



### Description

Used for window lighting of landscape buildings, ancient buildings, hotels, bridges, subway stations, entertainment venues, etc., including landscape decoration such as outdoor steps;

### Features

- \*The unique exterior design shows high-end atmosphere and elegance;
- \*Good heat dissipation of the highly conductive aluminum heat sink;
- \*Reflect the characteristics of the frame of the light-shaped structure object, making a door frame-shaped arch effect;
- \*The linear light gives the subject a strong sense of outline and spatial hierarchy, and an all-angle halo is created through the optical lens and the perfect optical design of the product;
- \*Whether you look from outside or inside the window, there will be no glare;
- \*Built-in constant current drive circuit: maintain efficient light emission; wide voltage stable operation, improve surge resistance, avoid flickering of lamps when external power supply voltage changes; during the series connection of lamps, ensure the brightness of the first and last lamps is consistent.

### Specification

Input voltage/power	DC24V / 8W
Light source	CREE/ 4 PCS
Beam angle	3*180°
Color temperature	3000K
Light effect	≥30lm/W
Color rendering index	Ra≥80
Color tolerance	SDCM≤5
Light source life	50000H
Control method	ON/OFF
IK grade	Ik08
IP rating	Ip66
Shell material	Aluminum + transparent PC
Exterior color	Sand Gray
Installation	Screw fixing
Product size (L×W×H)	160*57*80mm
Product size (L×W×H)	535*375*305mm
Net weight/gross weight	0.63kg/33kg(48PCS)
Working temperature	-20°C ~ 45°C