



LED Windowsill Light

TL-LH5207



Description:

It is mainly applicable to windowsill lighting of landscape buildings, ancient buildings, hotels, bridges, subway stations, entertainment venues, as well as landscape decoration of outdoor steps.

Feature:

- * Unique appearance design, full of high-end temperament.
- * High-conductivity aluminum radiator for good heat dissipation.
- * Suitable for the frame-shaped structure object, making a frame-shaped arch effect.
- * The linear light gives the subject a strong sense of contour and spatial hierarchy, and a full-angle halo can be formed through the combination of optical lenses and perfect lighting design.
- * No dazzling glare whether viewed from the outside or inside the window.
- * Built-in constant current driving circuit, allowing it to maintain efficient illumination. It operates stably over a wide voltage range, improving surge protection capability and avoiding flickering of the lights caused by changes in the external power supply voltage. During the process of connecting the lights in series, it ensures consistent brightness between the first and last light fixtures.

Specifications

| | |
|-------------------------|---------------------------|
| Input voltage/power | DC24V/12W |
| Light source | CREE/6PCS |
| Beam angle | 3*180° |
| Color temperature | RGB |
| Light effect | ≥20lm/W |
| Color rendering index | Ra≥50 |
| Color tolerance | SDCM≤5 |
| Light source life | 50000H |
| Control mode | DMX512 |
| IK level | IK08 |
| IP level | IP66 |
| Shell material | Aluminum + Transparent PC |
| Appearance color | sand gray |
| Installation method | screw fixed |
| Product Size | 160*57*80mm |
| Package Size | 535*375*305mm |
| Net weight/Gross weight | 0.63kg/33kg(48PCS) |