



# LED Walkway Light

## TL-LH5412



### Description:

It can be installed on sidewalks, pedestrian streets, promenades, corridors, walls, and stairs to achieve landscape decoration and lighting effects for roads, squares, villas, scenic spots, parks, etc.

### Feature:

- \* Unique appearance design, full of high-end temperament.
- \* High-conductivity aluminum radiator and integrated structure, good heat dissipation; it can effectively solve the problem that water droplets are easily condensed on the inner surface of the glass of similar products, which will affect the optical effect and accelerate the light decay.
- \* Scene effect: the light turns on as soon as people come, and goes out as soon as people leave; it can realize human intelligence and light chasing effect, and control the glare function.
- \* Most of this series of products support ON/OFF, radar sensing, DMX512 and other functions to meet the needs of different users.
- \* Built-in constant current driving circuit, allowing it to maintain efficient illumination. It operates stably over a wide voltage range, improving surge protection capability and avoiding flickering of the lights caused by changes in the external power supply voltage. During the process of connecting the lights in series, it ensures consistent brightness between the first and last light fixtures.

### Specifications

|                         |                                    |
|-------------------------|------------------------------------|
| Input voltage/power     | DC24V/6W                           |
| Light source            | Sanan/3PCS                         |
| Beam angle              | 10°(15°、30°、45°、60°、120° optional) |
| Color temperature       | RGBW(W=5700)                       |
| Light effect            | ≥50lm/W                            |
| Color rendering index   | Ra≥60                              |
| Color tolerance         | SDCM≤5                             |
| Light source life       | 50000H                             |
| Control mode            | DMX512                             |
| IK level                | IK08                               |
| IP level                | IP67                               |
| Shell material          | Aluminum + tempered glass          |
| Appearance color        | sand gray                          |
| Installation method     | screw fixed                        |
| Product Size            | 128*128*48mm                       |
| Package Size            | 625*290*295mm                      |
| Net weight/Gross weight | 0.75kg/32.5kg(40PCS)               |