



LED Walkway Light

TL-LH5417



Description:

It can be installed on sidewalks, pedestrian streets, promenades, corridors, walls, and stairs to achieve landscape decoration and lighting effects for roads, squares, villas, scenic spots, parks, etc.

Feature:

- * Unique appearance design, full of high-end temperament.
- * High-conductivity aluminum radiator and integrated structure, good heat dissipation; it can effectively solve the problem that water droplets are easily condensed on the inner surface of the glass of similar products, which will affect the optical effect and accelerate the light decay.
- * Scene effect: the light turns on as soon as people come, and goes out as soon as people leave; it can realize human intelligence and light chasing effect, and control the glare function.
- * Most of this series of products support ON/OFF, radar sensing, DMX512 and other functions to meet the needs of different users.
- * Built-in constant current driving circuit, allowing it to maintain efficient illumination. It operates stably over a wide voltage range, improving surge protection capability and avoiding flickering of the lights caused by changes in the external power supply voltage. During the process of connecting the lights in series, it ensures consistent brightness between the first and last light fixtures.

Specifications

Input voltage/power	DC24V/12W
Light source	CREE/6PCS
Beam angle	Bidirectional light output 10° (15°, 30°, 45°, 60°, 120° optional)
Color temperature	2700K (3000K, 4000K, 5000K, 5700K optional)
Light effect	≥80lm/W
Color rendering index	Ra≥80
Color tolerance	SDCM≤5
Light source life	50000H
Control mode	ON/OFF
IK level	IK08
IP level	IP67
Shell material	Aluminum + tempered glass
Appearance color	sand gray
Installation method	screw fixed
Product Size	128*128*48mm
Package Size	625*290*295mm
Net weight/Gross weight	0.8kg/34.5kg(40PCS)