



### Description

Mainly used in building facades, squares, leisure sports fields, stages, billboards, rockeries, building exterior lighting, landscape lighting, signs and indicator lighting, entertainment venues and stage lighting, bridges, etc.

### Feature

- \*Unique structural design: The overall appearance is simple, exquisite, and beautiful. The fully potted glue waterproof design ensures the stable operation of the lamp in various harsh weather conditions.
- \*High-quality material application: The lamp body is made of 6063 aluminum alloy and fastened with SUS304 stainless steel screws. A variety of installation methods are available. The surface adopts outdoor grade electrostatic spraying, which has excellent corrosion resistance and is very suitable for use in harsh outdoor environments.
- \*Excellent optical performance: The external anti-UVPC cover effectively improves the light mixing effect of the lamp, ensures uniform light distribution, and creates a comfortable visual experience for the lighting scene.
- \*Multiple light source options: optional single color, RGB, RGBW beads, supporting DMX512 control system. Simple wiring design makes the installation and maintenance of lamps more convenient and faster.

### Specification

Input voltage/power	DC24V/12W
Light source	OSRAM/48PCS
Beam angle	120°
Color temperature	3000K (1900K, 2100K, 4000K, 5700K optional)
Luminous efficacy	≥50lm/W
Color render index	Ra≥80
Color tolerance	SDCM≤5
Light source lifespan	50000H
Control method	DMX512/4 band
IK class	Ik08
IP class	Ip65
Housing Material	Aluminum + milky white PC cover
Exterior color	sand gray
Installation method	Bracket screw fixation
Product dimension (L×W×H)	1000*31.4*56mm
Packaging dimension (L×W×H)	1055*335*310mm
Net weight/gross weight	0.57kg/16kg(24PCS)