



LED Wall Washer

TL-LH1403



Description

The wall washer is suitable for panoramic floodlighting of internal and external walls such as government lighting projects, commercial places, stages, conference rooms, display lights, ancient buildings, cultural squares, overpasses, building exterior walls, architectural landmarks, etc. It is also applicable to landscape buildings, outdoor squares and so on.

Features

- * High-power wall washer, stylish and beautiful appearance. Enlarged heat dissipation structure design fully guarantee the stability of LED and long lifespan;
- * The fixture is made of 6063 aluminum alloy mold, the surface is anodized, and the lampshade is made of high-strength semi-toughened glass with impact resistance, friction resistance and excellent rainwater cleaning ability.
- * No glue and waterproof design;
- * Imported LED light source, high luminous flux output, good light color consistency, constant current design; RGB gray level is high, making the dynamic dimming effect softer and colorful;
- * Good electromagnetic compatibility, no electromagnetic interference to the surrounding environment.
- * Built-in constant current driving circuit, allowing it to maintain efficient illumination. It operates stably over a wide voltage range, improving surge protection capability and avoiding flickering of the lights caused by changes in the external power supply voltage. During the process of connecting the lights in series, it ensures consistent brightness between the first and last light fixtures.

Specifications

| | |
|---------------------------------|---|
| Input voltage/power | DC24V/6W |
| Light source | LUMILEDS/6PCS |
| Beam angle | 10°60°(15°、30°、45°、60°optional) |
| Color temperature | 3000K(1900K、2100K、4000K、5700K optional) |
| Light effect | ≥80lm/W |
| Color rendering index | Ra≥80 |
| Color tolerance | SDCM≤5 |
| Light source life | 50000H |
| Control method | DMX512 |
| IK Class | IK08 |
| IP Class | IP65 |
| Shell material | Aluminum + tempered glass |
| Shell color | Sand gray |
| Installation method | Bracket screws |
| Product size (L×W×H) | 300*46*108mm |
| Packaging size (L×W×H) | 395*380*280mm |
| Net weight/Gross weight | 0.6kg/9kg(12PCS) |
| Remark | Light baffle optional |
| Working environment temperature | -20 C ~45 C |