



## Description

Mainly used in building facades, squares, leisure sports fields, stages, billboards, rockeries, building exterior lighting, landscape lighting, signs and indicator lighting, entertainment venues and stage lighting, bridges, etc.

## Feature

- \*Unique structural design: adopts internal cavity heat dissipation, with a simple and angular appearance, showing unparalleled exquisite beauty.
- \*High-quality material: Aluminum alloy lamp body, with double slider fastening bracket, the surface is treated with outdoor-grade electrostatic spraying to ensure strong corrosion resistance and can easily cope with various harsh outdoor environments.
- \*Excellent optical configuration: imported light sources are used to show excellent light color performance and greatly improve the light output efficiency of the lamp. In addition, anti-glare shading plates can be selected to ensure soft light without glare.
- \*Diverse lamp bead selection: Provide monochrome, RGB (3 in 1), RGBW (4 in 1) and other lamp bead selections to meet different needs. At the same time, it supports DMX512 control system, and the simple wiring design makes the installation and maintenance of lamps easy and convenient.

## Specification

Input voltage/power	DC24V/18W
Light source	Sanan/18PCS
Beam angle	20°45°(30°, 45°, 60° optional)
Color Temperature	RGB
Light Effect	N/A
Color rendering index	N/A
Color Tolerance	SDCM≤5
Light source lifespan	50000H
Control method	DMX512/3 segments
IK class	Ik08
IP class	Ip65
Housing Material	Aluminum + tempered glass
Exterior color	Sand Gray
Installation	Bracket screw fixing
Product dimension (L×W×H)	1000*40*66mm
Package dimension (L×W×H)	1055*335*285mm
Net weight/gross weight	0.97kg/22.3kg(20PCS)
Working temperature	-20°C ~ 45°C