



## Description

It is mainly used for building facades, squares, leisure sports fields, stages, billboards, rockery, building exterior lighting, landscape lighting, signs and indicative lighting, entertainment venues and bridges lighting, etc.

## Feature

- \*Unique structural design: adopts internal cavity heat dissipation, with a simple and angular appearance, showing unparalleled exquisite beauty.
- \*Made of high-quality materials: Aluminum alloy lamp body, with double slider fastening bracket, the surface is treated with outdoor grade electrostatic spraying to ensure strong corrosion resistance, and can easily cope with various harsh outdoor environments.
- \*Excellent light source configuration: imported light sources are used to show excellent light color performance and greatly improve the light output efficiency of the lamp. In addition, anti-glare shading panels can be selected to ensure soft light without glare.
- \*Diverse lamp bead selection: Provide monochrome, RGB (3 in 1), RGBW (4 in 1) and other lamp bead selections to meet different needs. At the same time, it supports DMX512 control system, and the simple wiring design makes the installation and maintenance of lamps easy and convenient.

## Specification

Input voltage/power	DC24V/18W
Light source	Sanan/12PCS
Beam angle	20°45°(15°, 30°, 45°, 60° optional)
Color temperature	RGBW
Light effect	≥50lm/W
Color rendering index	Ra≥70
Color tolerance	SDCM≤5
Light source life	50000H
Control method	DMX512/2 segments
IK grade	Ik08
IP rating	Ip65
Shell material	Aluminum + tempered glass
Exterior color	Sand Gray
Installation	Bracket screw fixing
Product size (L×W×H)	500*40*66mm
Packing size (L×W×H)	555*335*285mm
Net weight/gross weight	0.55kg/12.8kg(20PCS)
Working temperature	-20°C ~ 45°C