



### Description

It is widely used in eaves of ancient buildings, balconies, pavilions, archways, fences, park trails, guardrails, signboards, commercial complexes, squares, theme parks, playgrounds, and other places.

### Feature

- \* Using a neat and light linear extruded aluminum lamp body, plus a shade cover, it can ensure the light transparency on the wall, without hindering the view and not affecting the indoor lighting of the building.
- \* Ultra-narrow design, about the size of an adult's little finger, with high cost performance. It has very little impact on the building during the day when installed, and can basically be hidden in the crack of the wall.
- \* Hidden cable design: Connected by the incoming and outgoing lines with double-headed male and female waterproof connectors.
- \* 50m connection, seamless splicing, no color difference.
- \* Simple rotating bracket, optional fixed bracket, stainless steel buckle and other installation methods.
- \* Surface treatment can be determined based on user needs to better fit with the building.

### Specifications

Input voltage/power	DC24V/3W
Light source	OSRAM/10PCS
Beam angle	35°
Color temperature	3000K(1900K、 2100K、 4000K、 5700K optional)
Light effect	≥80lm/W
Color rendering index	Ra≥80
Color tolerance	SDCM≤5
Light source life	50000H
Control method	ON/OFF
IK Class	IK06
IP Class	IP67
Shell material	Aluminum
Shell color	Sand gray
Installation method	Fixed (optional embedded buckle installation)
Product size (L×W×H)	300*17*57mm
Packaging size (L×W×H)	350*340*330mm
Net weight/Gross weight	0.2kg/8.5kg(30PCS)
Remark	With light baffle