



LED Wall Washer

TL-LT621A



Features

- * Color: RGBW stepless color mixing.
- * Dimming: 0-100% linear adjustment.
- * Strobe: electronic strobe, 0-25 times/sec.
- * DMX512 port program update, convenient and fast software upgrade through DMX data cable.
- * Over-temperature protection function: built-in NTC temperature control function; when the LED is overheated, the output power of the LED is intelligently reduced.
- * Starry sky effect: light and dark linear transformation of starry sky effect

Specifications

Model	TL-LT621A
Input voltage	AC 110-240V 50/60Hz, 80W
Light source	6*15W (RGBW) 4 in 1 LED + 3*1W Monochrome Laser (R1 G1 B1)
Average lifespan	50000H
Color temperature	6500K
Beam angle	20°
Control mode	The control box is needed; comply with the international standard DMX512 signal control protocol, 3-core DMX512 signal interface; master-slave synchronous control mode, support RDM protocol and program online update function
Operation mode	Built-in 3 operation modes (DMX mode, user program mode, built-in program mode)
Channel	7/13/33 channels
Lamp material	High-strength extruded aluminum + die-casting aluminum alloy cover
Protection class	IP65
Working temperature	-20°C~45°C
Fixture size (L×W×H)	562×119×167.5mm
Packaging size (L×W×H)	635×240×190mm
Gross weight	5.5kg
Net weight	4.6kg