



LED Linear Light

TI-PL601



Description :

It is suitable for lighting solutions in the front desk, open office area, passage, general conference room, video conference room, independent office room, leisure area, toilet, public business hall, lobby, parking lot, etc.

Feature :

- * High-quality PC light-transmitting cover, good light transmittance, uniform light without yellow light/bright line, soft light color;
- * Through-type reinforcing ribs, high mechanical strength, not easily deformed;
- * Stable and reliable LED lamp beads, the lamp lifespan is up to 20000H;
- * Microcrystalline anti-glare design, UGR<16;
- * Adopt SELV (safety extra low voltage), safe and reliable;
- * Super energy-saving, the max total light efficiency reaches 100lm/W, Ra \geq 80 ultra-high energy-saving rate;
- * External high conversion efficiency isolated 0-10V dimming drive power supply, with dimming range up to 15-100%, smooth dimming without flicker, good compatibility, high precision, high adaptability of dimming switch, power factor up to 0.9;
- * No visual flicker, anti-blue light, healthier for the eyes.

Specification:

Model	TI-PL601
Input voltage/power	AC220V~50Hz/36W
Light source	Philips 3030
Beam angle	120°
Color temperature	3200K~6500K
Color	Color coated steel plate white/black/PC cover
Control mode	0-10V dimming
Installation method	Line suspension / boom / square tube / bridge / ceiling
Protection class	IP20
Product size	150*1200*65mm
Package size	1265*270*320mm
Net weight	1.7kg
Gross weight	5.3kg (2PCS/box)