



Feature

- * DMX512 channel number: 1024
- * Number of computer lights to be connected: 100
- * The maximum available control channels for each computer light: 120 main channels (including fine-tuning channels)
- * Number of scenes that can be saved: 100
- * Number of scenarios that can be run simultaneously: 10
- * Total number of steps in multi-step scenario: 1000
- * Number of graphics that can be stored in each scene: 5
- * Number of graphics that can be run simultaneously: 10
- * Light library: Supports Pearl R20 light library, and the console can automatically generate a light library for lighting equipment from the same manufacturer.
- * Scene time control: fade in, fade out, LTP slide
- * Graphic generator: can generate Dimmer, P/T, RGB, CMY, Color, Gobo, Iris, Focus and other graphics
- * Master fader: global, playback, lighting fixtures
- * U disk reading: supports FAT32 format
- * Control method: Art-net protocol and RDM protocol
- * Support the re-matching of address codes for scanner lights
- * Support horizontal and vertical exchange of lamps
- * Support lamp channel inverting output
- * Support lighting channel sliding mode switching
- * Support interlocking scenes, point control scenes, and immediate blackout
- * Support turntable and fader to adjust channel value
- * Support fader to start the scene and adjust the light
- * Physical control: 68 buttons, 11 faders, 3 encoders
- * Remote control: supports remote control of handheld devices, compatible with IOS/ANDROID handheld terminal systems
- * Intelligent light control system: Equipped with an intelligent light control system, controlled and managed through the Web
- * Operating language: Supports Simplified Chinese, English can be switched at will
- * Backlight keyboard: Full backlight lighting programming keyboard, easy to use in dark environment, precise control
- * Screen display: 3.5-inch HD LCD display with clear content display and equipped with a new UI interface design, which uses pictures and texts to make it easier for users to understand and operate

Specification

Input voltage	AC 110-240V/50-60Hz
Rated power	3.6W
Product size (L×W×H)	372×244×64mm
Carton size (L×W×H)	420×290×120mm
Gross weight	3.9kg
Net weight	3kg