



Console

TL-SL711



Feature:

- * 1024 DMX channels, and 2 photoelectric isolation DMX output ports.
- * 7" TFT-LCD touch screen, Chinese and English operation interface.
- * Backlight keys, with three backlight color combinations.
- * 4 photoelectric data control wheels with backlight.
- * 15 playback program fader × 40 pages, a total of 600 playback programs can be stored. A maximum of 15 playback programs can be output at the same time.
- * A maximum of 400 lamps can be controlled.
- * A maximum of 400 lamp groups can be stored.
- * A maximum of 400 material data can be edited.
- * A maximum of 400 user graphics can be stored.
- * A maximum of 400 records of macro performances can be stored.
- * Multi-option keypad. Multiple options such as groups, lamps, materials, user graphics, and macro performances are provided. It is convenient for users to do multi-page selections with the touch screen.
- * Independent color mixing system control wheel. It is especially convenient to control LED lights and computer lights with CMY or RGB channels.
- * Built-in various graphics running effects, provide a variety of parameter settings to create endless changes, and support being saved as user graphics.
- * Provide the program priority function; the performance program can be individually set to 5 levels: lowest, low, normal, high, and highest, and the higher one will run first.
- * Built-in nearly 8000 kinds of computer light library data, compatible with R20 lamp library. The user can edit the system lamp library or create a new user lamp library.
- * Support the standard MIDI device control, support multiple consoles working together in a master-slave manner, and support the console accepting external MIDI time code trigger function.
- * The website supports free download of upgrade files such as lamp library and system version.
- * Built-in electronic hard disk supports performance program backup and running data storage.
- * With a USB interface, you can use a U disk to store multiple user performance files and system backup files.
- * Dimmable 12V gooseneck work light.

Specifications:

Model	TL-SL711
Input voltage	AC 110-240V 50/60Hz
Fixture size (L×W×H)	482×445×180mm
Package size (L×W×H)	540×260×560mm
Gross weight	19.5kg
Net weight	9.3kg