



Feature

- *Function: Equipped with 1 independently rotating stripe column, supporting infinite forward and reverse rotation and adjustable speed.
- *Color mixing system: Using a uniform RGBW color mixing system to create infinite dynamics and infinite color changing effects.
- *Dimming: 0-100% linear adjustment to meet brightness needs in different scenes.
- *Strobe: 0-25Hz electronic strobe, built-in pulse stroboscopic effect.
- *Over-temperature protection function: Built-in NTC temperature control function, when the LED is overheated, the output power of the LED is intelligently reduced to ensure the service lifespan of the LED.
- *Display: Equipped with a 1.6-inch LCD blue screen display. You can query the lamp software version number and other information through the display screen to facilitate management and maintenance.

Specification

Input voltage	AC 110-240V 50/60Hz, 120W
Light source	4*30W (RGBW)OSRAM LED
Average lifespan	50000H
Color temperature	6000K
Spot angle	10°
Control method	Complies with international standard DMX512 signal control protocol, 3-core (optional 5-core) DMX512 signal interface; master-slave synchronous control mode, supports RDM protocol and program online update function
Operating mode	3 operating modes (DMX mode, user program mode, built-in program mode)
Channel	5/9/21 Channel
Lamp materials	High-strength extruded aluminum + die-cast aluminum alloy cap
Protection class	Ip67
Working temperature	-20°C ~ 45°C
Lamp dimension (L*W*H)	1000×140×174mm
Packaging dimension (L*W*H)	1095×520×275mm
Gross weight	15.3kg (2pcs)
Net weight	4.95kg