



LED Flood Light

TL-LT611



Feature:

- * Strobe: independent electronic strobe 1-25Hz, support random strobe, pulse strobe, synchronous and asynchronous strobe, single color and mixed color temperature strobe.
- * Color mixing: RGBW (red, green, blue and white) linear color mixing, 16.7 million colors (0-100% saturation adjustment), and built-in macro function.
- * Electronic dimming: 0-100% independent electronic linear dimming, lifelike and flicker-free camera video, the master-slave self-propelled automatic synchronization function, and the console normally controls the self-propelled permanent synchronization.
- * LCD menu: invoke various scenes, built-in programs can be directly invoked and executed.
- * Fixture connection: three-pin signal line IN/OUT and power line IN/OUT.
- * Cast aluminum housing, high light efficiency, uniform light mixing, stable performance; equipped with 1m hand in hand power supply and signal line of 1 in and 1 out; 1024-level ultra-high grayscale dimming is softer.

Specifications:

| | |
|----------------------|---|
| Model | TL-LT611 |
| Input voltage | AC 110-240V 50/60Hz, 360W |
| Light source | 108×3W LED(R27G27B27W27)) |
| Average lifespan | 50000H |
| Color temperature | 3200K~7200K linear adjustment |
| Beam angle | 25°(8/15/45/60°optional) |
| Control mode | Multiple voice control, DMX512, built-in program self-propelled, master-slave connection mode |
| Channel | 3/7 channels |
| Fixture material | Cast aluminum housing |
| Protection class | Fireproof V-1, protection IP65 |
| Fixture size (L×W×H) | 715×310×340mm |
| Net weight | 18.5kg |
| Working temperature | -20°C~45 °C |