



Moving Head Beam Light

TL-LT821



Feature:

- * Various preset dynamic virtual pattern effects, bidirectional rotation, adjustable speed.
- * Various preset static virtual pattern effects.
- * The foreground color of the dynamic/static virtual pattern is optional, the color temperature is adjustable, and it supports dimming.
- * The background color of the dynamic/static virtual pattern is optional, the color temperature is adjustable, and it supports dimming.
- * Dimming system 0~100% smooth linear LED dimming.
- * Support horizontal/vertical rotation and correction.
- * RGBW stepless color mixing.
- * Uniform light spot, pure color mixing, delicate and full light color.
- * Built-in 33 color macro function effects.
- * 7 built-in self-propelled programs.
- * The screen is equipped with a battery, and can be used for the address code setting and other settings in the menu.
- * With DMX signal monitoring indicator.
- * The screen can be flipped by 180°.
- * Automatic screen off function.
- * High-efficient and noise-free five-fan natural cooling system, cooling aluminum/copper + liquid/fan.
- * Support the display and management of the working temperature of the light.
- * The over temperature protection function can reduce the lamp bead power to ensure the normal use.

Specifications:

Model	TL-LT821
Input voltage	AC110V-240V 50/60Hz, 960W
Light source	19*40W LED
Color temperature	2800K-3200K tungsten lamp simulation effect, 3200K-8000K linear color temperature adjustment
Average lifespan	20000H
Beam angle	Beam angle 3°-30°, spot angle 6°-40°
Control mode	International standard DMX512 signal; DMX512, master-slave, voice control or self-propelled operation, Art-NET control (optional) built-in imported DMX wireless receiver (optional)
Channel	14/20/30/37 channel
Power supply	Waterproof power line input and output, with switch and fuse holder
Signal input	Input signal isolation protection function to ensure stable signal transmission without interference
Network interface	Waterproof RJ45 Ethernet connector input and output (optional)
Signal line	Waterproof signal line input and output
Screen	2.4-inch HD TFT LCD touch screen
Protection class	IP65
Fixture size (L×W×H)	393×298×534mm
Package size (L×W×H)	645×405×505mm
Gross weight	25kg