



Moving Head Light

TL-LT886A



Feature

- * Dimming: 0-100% linear dimming.
- * Color wheel: 7 color gels + white light, bidirectional stepless rotation, magnet positioning, color index, half-color and other functions.
- * Gobo wheel: 6 rotating gobo wheels, 6 gobos; gobo positioning, rotation, dithering and other effects.
- * Cutting system: It can cut graphics including triangles, squares, parallelograms, and semicircles; the cutter pattern supports bidirectional 90° rotation and flexible positioning functions according to the scene.
- * Aperture function: Zoom-in and zoom-out dynamic effects can be achieved.
- * Adjustable focus: DMX linear focusing, ultra-fine and smooth focus adjustment.
- * Prism: Optional triangular prism, rectangular prism, and four-row lens, etc.
- * Atomization: 10%-100%.
- * Strobe: Electronic strobe, 0-25 times/sec (built-in pulse strobe effect).
- * Scanning range: Horizontal 540°, vertical 270°, with auto return function.
- * Display interface: 2.8-inch LCD widescreen Chinese and English interface, with flip function.
- * Other functions: The input signal has an isolation protection function to ensure stable signal transmission without interference; built-in NTC temperature control function, when the LED is overheated, the output power of the LED will be intelligently reduced; it supports software upgrade through the DMX data line; the lamp usage time, bulb usage time and software version number can be displayed.

Specification

Model	TL-LT886A
Input voltage	110V~240V AC, 50/60Hz
Rated power	1300W@220V
Light source	1pcs 1050W white light LED module Osram chip
Color temperature	6800K±300K, CRI≥95
Service lifespan	≥20000H
Beam angle	5°-50°
Control mode	International standard DMX512 signal, 3-core signal line (five-core optional) DMX512 interface; DMX wireless function optional; 4 operation modes (DMX mode, self-propelled mode, manual mode, stand-alone editing mode); support RDM protocol and program online update function
Channel	28/14 channels
Fixture material	High temperature resistant engineering plastic + cast aluminum/wire-drawing aluminum material + copper tube radiator + waterproof fan for heat dissipation
Working temperature	-20°C ~ 45°C
Protection class	Ip66
Fixture size (L×W×H)	457×320×768mm
Package size (L×W×H)	690×540×735mm
Gross weight	51KG
Net weight	45KG