



Moving Head Beam Light

TL-SL113B



Feature:

- * Color wheel: 11 color gels + 1 white light, colorful lens + atomization, CMY+CTO linear wireless color.
- * Fixed gobo wheel: 17 fixed gobos + 1 white light, pattern dithering, one-way flow effect, adjustable speed, and flexible positioning function.
- * Rotating gobo wheel: 8 rotatable gobos + 1 white light, two-way rotation, pattern dithering and water flow effects.
- * Focusing: ultra-smooth electronic focusing.
- * Prism: hexadecagon prism + 2 trapezoidal lenses, two-way rotation, and adjustable speed.
- * Strobe: the maximum stroboscopic speed is 20 times/sec, and random or pulse strobe is optional.
- * Atomization: 0-100% soft light effect.
- * Scanning range: X-axis 540°/2.5S, Y-axis 270°/1.5S; resolution: 16Bit.
- * Display interface: a 2.8-inch widescreen LCD interface in Chinese and English that can be flipped; menu button supports the setting of over-temperature protection; by charging the mobile power supply through the MICRO USB port, the address code can be set, and no need to connect to the power supply.
- * Other function: the input signal has an isolation protection function to ensure stable signal transmission without interference; with intelligent over temperature protection, the light is automatically turned off when it is overheated.

Specifications:

Model	TL-SL113B
Input voltage	AC110V-240V 50/60Hz, 600W
Ballast	Electronic ballast
Light source	OSRAM SIRIUS HRI 461W
Average lifespan	2000H
Beam angle	Zoom /2° Spot/7- 40° Wash/ 7-45°
Control mode	DMX512 protocol, compatible with RDM function, support online program update
Channel	24/29/36 channels
Fixture material	High temperature resistant plastic + molded alloy material
Protection class	IP20
Fixture size (L×W×H)	389×267×688mm
Package size (L×W×H)	480×460×785mm
Gross weight	28.5kg
Net weight	25.5kg