



Moving Head Beam Light

TL-SL162



Feature:

- * Optics: three sets of optical lenses (3-layer coating) with high temperature resistance and strong light transmittance.
- * Color wheel: 8 color gels + 1 white light, bidirectional rainbow effect, adjustable speed, flexible positioning function.
- * Fixed gobo wheel: 11 fixed gobos + 1 white light, one-way flowing water, adjustable speed, flexible positioning function.
- * Rotating gobo wheel: 7 replaceable gobos + white light.
- * Focusing: Electronic automatic focusing.
- * Prism: triangular rotating prism, bidirectional rotation, and adjustable speed.
- * Strobe: synchronous, asynchronous and random strobe modes, and adjustable speed.
- * Atomization: 1 independent atomization effect, the light spot is soft and natural.
- * Scanning range: X-axis 630°/2.7 S (optional 630°), Y-axis 270°/1.5 S, precise scanning and positioning.
- * Display interface: a wide-screen 2.4-inch LCD interface in Chinese and English, with rechargeable battery, you can enter the menu to set the address code and perform other settings without powering on; the menu is hierarchically structured and has a friendly graphical interface.
- * Intelligent heat dissipation: using wind direction drainage and temperature intelligent monitoring technology, built-in NTC temperature control function, when the LED is overheated, it will intelligently reduce the output power.

Specifications:

Model	TL-SL162
Input voltage	AC110V-240V 50/60Hz, 170W
Light source	120W LED
Average lifespan	50000H
Color temperature	8000K
Beam angle	11~21°
Control mode	DMX512 protocol, support RDM protocol and program online update function, support Art-net Ethernet data interface (DMX wireless function optional)
Channel	17/15 channels
Fixture material	High temperature plastic + molded alloy material
Protection class	IP20
Fixture size (L×W×H)	310×210×461mm
Package size (L×W×H)	385×365×490mm
Gross weight	13.3kg
Net weight	10.7kg