



Moving Head Beam Light

TL-SL172



Feature

- * Optics: Use high temperature resistant and highly transmittance optical lenses (3 layers of coating), two groups of lenses.
- * Color wheel: 11 color gels + 1 white light, two-way rainbow effect, adjustable speed, flexible positioning function.
- * Fixed gobo wheel: 14 fixed gobos + 1 white light, one-way flow, adjustable speed, flexible positioning function.
- * Prism: Octagonal rotating prism + four-row lens, two-way rotation, superimposition, adjustable speed.
- * Strobe: With synchronous, asynchronous, and random strobe modes, adjustable speed.
- * Atomization: 1 independent atomization effect, the light spot is soft and natural.
- * Scanning range: X-axis 630°/2.7 S, Y-axis 270°/1.5 S, accurate scanning positioning.
- * Display interface: 2.4-inch LCD widescreen interface in Chinese and English; with a rechargeable battery, you can enter the menu to set the address code and perform other settings without powering it on; the menu is hierarchical and the graphical interface is user-friendly.
- * Intelligent heat dissipation: Using wind direction drainage and intelligent temperature monitoring technology, built-in NTC temperature control function, when the LED is overheated, the output power of the LED will be intelligently reduced.

Specification

Model	TL-SL172
Input voltage	AC110V-240V 50/60Hz, 250W
Light source	Appotronics 200W LED Module
Average lifespan	50000H
Color temperature	10000K
Beam angle	2.0°
Control mode	DMX512 protocol, support RDM protocol and program online update function, support Art-net Ethernet data interface (DMX wireless function optional)
Channel	15/13 channels
Fixture material	High temperature resistant plastic + molded alloy material
Protection class	Ip20
Fixture size (L×W×H)	310×210×466mm
Package size (L×W×H)	385×365×490mm
Gross weight	15.1kg
Net weight	12.5kg