



Moving Head Beam Light

TL-SL185



Feature:

- * Optics: high-precision glass optical lens (6-layer coating), electronic focusing for multi-level optical lens groups, linear magnification function.
- * Color mixing system: 1 color wheel: 11 color gels + 1 white light, rainbow effect with two-way rotation, adjustable speed, flexible positioning function.
- * Pattern system: 1 rotatable gobo wheel: 7 pluggable gobos + white circle, with pattern dithering and flexible positioning function; 1 fixed gobo wheel: 11 fixed gobos + 2 white light, two-way flow, adjustable speed, flexible positioning function.
- * Dynamic effect wheel: flame effect, water pattern effect, two-way flow, flexible positioning function.
- * Prism: 3 rotating prisms, support bidirectional rotation, superimposition, and adjustable speed.
- * Strobe: electronic strobe 1-13 times/sec, synchronous, asynchronous, and random stroboscopic mode, and adjustable speed.
- * Atomization: 1 independent atomization effect, soft and natural light spot.
- * Scanning range: X-axis 540°/630°3.3S, Y-axis 270°/2.0S, precise scanning and positioning.
- * Display system: a 2.8-inch touch screen, with a power bank, you can enter the menu for address code setting and other settings; the buttons will be automatically locked after 15 seconds of standby to prevent accidental operation; long press the menu button for 3 seconds to activate the button reset and detection setting; long press the Left and Right buttons to lock the horizontal and vertical scanning and reset.
- * Smart heat dissipation: using wind drainage and smart temperature monitoring technology, according to the temperature of different parts of the fixture, the cooling fans inside the fixture are automatically driven to effectively cool different components.
- * CMY color mixing system: CMY+CTO color gels, stepless mixed color + CTO, color temperature can be adjusted according to the scene.
- * Gyroscope: when the gyroscope function is turned on, the Y axis is automatically compensated and calibrated; the autofocus is supported within 3-25.5 meters.

Specifications:

Model	TL-SL185
Input voltage	AC110V-240V 50/60Hz, 600W
Light source	450W LED Module BEAM
Average lifespan	20000H
Color temperature	7800K
Beam angle	5°~40°
Control mode	DMX512 protocol, support RDM protocol and program online update function; support Art-net Ethernet data interface; USB dial code setting (optional DMX wireless function)
Channel	26/20 channels
Fixture material	High temperature resistant plastic
Protection class	IP30
Fixture size (L×W×H)	385×270×666.5mm
Package size (L×W×H)	470×355×745mm
Net weight	20kg
Gross weight	23.5kg