



Features

- *Optics: Combined optical lens
- *Color system: RGBW infinite color mixing, with color macro function
- *Auxiliary light effects: strobe, marquee effect, with built-in program
- *Zoom angle: 4-37° linear zoom
- *Color temperature: 2500-8000K linearly adjustable
- *Dimming: 0-100% smooth dimming
- *Strobe: Electronic strobe, 0-15 times/second (built-in pulse strobe effect)
- *Light body rotation angle: Y axis 270° electric control (8bit/16bit precision scanning)
- *Display: LCD display, Chinese and English bilingual system
- *Special functions: support RDM function, support software update via DMX connection

Specification

Input voltage	AC110-240V 50/60Hz, 760W
Light source	Main light: 10 60W RGBW 4-in-1 LED light beads, auxiliary light: 82 0.25W 5050RGB colorful side-emitting LED strip light
Average lifespan	50000H
Control mode	Self-propelled, DMX512, built-in program, master-slave, voice control
Channel	17CH/27CH/99CH/108CH/168CH/170CH
Lighting material	High-strength heat-resistant engineering plastic shell and metal powder spraying technology
Protection level	Ip20
Light size (L×W×H)	1002×115×285mm
Packing size (L×W×H)	1080×380×395mm
Gross Weight	40.3kg(2PCS)
Net weight	18.5kg