



## Features

Side 1 (main light-flood light):

\*Optics: Combined optical lens

\*Color system: RGBW infinite color mixing, with color macro function

\*Light projection angle: 4-37° linear zoom

Side 2 (auxiliary light-strobe):

\*Auxiliary light effects: strobe, dye, running effect, with built-in program

\*Dimming: 0-100% smooth dimming

\*Strobe: Fast electronic strobe 1-20Hz (built-in pulse strobe effect)

\*Lamp body rotation angle: XY axis infinite rotation

\*Display: LCD display, Chinese and English bilingual system

\*Special functions: support RDM function, support software update via DMX connection

## Specification

<b>Side 1 (main light-flood light)</b>	
<b>Light source</b>	5 60W RGBW 4-in-1 LED light sources
<b>Side 2 (auxiliary light-strobe)</b>	
<b>Light source</b>	42 3535 LED high brightness white light, 84 5050 RGB LED light beads
<b>Input voltage</b>	AC110-240V 50/60Hz, 360W
<b>Average lifespan</b>	50000H
<b>Control mode</b>	Self-propelled, DMX512, built-in program, master-slave, voice control
<b>Channel</b>	26CH/68CH
<b>Lighting material</b>	High-strength heat-resistant engineering plastic shell and metal powder spraying technology
<b>Protection level</b>	Ip20
<b>Lamp size (L×W×H)</b>	534×225×439mm
<b>Packing size (L×W×H)</b>	615×445×315mm
<b>Gross weight</b>	15.8kg(1PCS)
<b>Net weight</b>	14.1kg