



Feature

1. Strobe: Independent electronic strobe 1-25Hz.
2. Electronic dimming: 0-100% independent electronic linear dimming, lifelike and flicker-free camera video, the master-slave self-propelled automatic synchronization function, and the console normally controls the self-propelled permanent synchronization.
3. LCD display menu: Call various scenes, and built-in programs can be directly called and executed.
4. Fixture connection: three-core signal line IN/OUT and power line IN/OUT.
5. Features: Cast aluminum * housing, high luminous efficiency, uniform light mixing, and stable performance; equipped with a 1.3m hand-in-hand power line and signal line of 1 in and 1 out.
6. Sound control sensitivity: 65-130dB.
7. Over-temperature protection function: Built-in NTC temperature control function, when the LED is overheated, the output power of the LED is intelligently reduced.

Specification

Input voltage	AC 110-240V 50/60Hz, 165W
Light source	54×3W LED(W54)
Average lifespan	50000H
Color temperature	3200K
Beam angle	25°(15°, 45° optional)
Control mode	A variety of voice control, DMX512, built-in program self-propelled, master-slave online mode, supports RDM protocol and program online update function
Channel	2 channels
Fixture material	Cast aluminum housing
Protection class	Fire protection V-1, protection Ip20
Fixture size (L×W×H)	287×215×330mm
Packaging size (L×W×H)	250×250×360mm
Gross weight	3.7kg
Net weight	3.2kg