



Static wash light

TL-SL207



Feature:

- * Strobe: independent electronic strobe 1-25Hz.
- * Color mixing: RGBW (red, green, blue and white) linear color mixing, 16.7 million colors (0-100% saturation adjustment), and built-in macro function.
- * Electronic dimming: 0-100% independent electronic linear dimming, providing flicker-free video for accurate recording, with master-slave automatic synchronization function. The control console allows normal control with permanent synchronization of the auto-follow feature.
- * LCD menu: invoke various scenes; built-in programs can be directly invoked and executed.
- * Fixture connection: three-core signal line IN/OUT and power line IN/OUT.
- * Features: cast aluminum housing, high light efficiency, uniform light mixing, stable performance, and comes with a 1.3-meter long power and signal cable with one input and one output hand grip.
- * Voice control sensitivity: 65-130dB.
- * Over-temperature protection function: Built-in NTC temperature control function, when the LED is overheated, the output power of the LED is intelligently reduced.

Specifications:

Model	TL-SL207
Input voltage	AC 110-240V 50/60Hz, 270W
Light source	120×3W LED(R30+G30+B30+W30)
Average lifespan	50000H
Color temperature	3200K~7200K linear adjustment
Beam angle	Beam angle 17°, spot angle 33°
Control mode	Multiple voice control, DMX512, built-in self-propelled program, master-slave online mode. Support RDM protocol and program online update function
Channel	4/8/9 channels
Fixture material	Cast aluminum housing
Protection class	Fireproof V-1, protection IP20
Fixture size (L×W×H)	328×267×294mm
Package size (L×W×H)	690×390×350mm
Gross weight	13.6kg(2PCS)
Net weight	5.6kg